



Shieldex[®] Ultrafle Tape with mask

17003211 x x

High conductive non woven

Material	Polyamide (PBN II) copper/tin-plated
Thickness	0.27 mm ± 10 %
Weight	90 g/m ² ± 10 %
Surface Resistivity	< 0.2 Ω/□ according ASTM IEEE
Width	6/8/10/12.5/20 mm (on demand)
Mask	Silicone, backing polyester film, Dielectric strength 7.5 kV(min 6.2kV), Adhesion to steel 3.5 N/cm (min. 2.5/N/cm) Thermal class B(130 °C)

Adhesive (conductive)

Adhesive	Acrylat adhesive conductive
Adhesion to steel	≥ 2 N/10 mm
Short time thermal resistance	120 °C
Resistivity	< 1 Ω

Adhesive (liner)

Material	Paper (white)
Width	0.037 mm ± 10 %
Storage	Cool and dry place, approx. 20 °C and 50-60 % relative humidity Storage period should not exceed 24 month
Temperature Range	-30 °C to 80 °C

Compliance and Certification DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 01.05.21/02 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.