



## Shieldex® Med-tex P130

1150902130

<b>Raw Material</b>	78 % Polyamide + 22 % Elastomer
<b>Type of knit</b>	Stretch-Tricot
<b>Metal Plated</b>	99.9 % Pure Silver
<b>Metal Content</b>	19.23 ± 2 % Silver
<b>Stretch</b>	Double stretch direction / elongation warp 55- 205 % / weft 85-125 %
<b>Abrasion Resistance</b>	≤ 9000 cycles
<b>Total Weight</b>	130 g/m <sup>2</sup> ± 18 %
<b>Total Thickness</b>	0.55 mm ± 15 %
<b>Roll Width</b>	132 ± 5 cm
<b>Roll Length</b>	Max. 36 m
<b>Temperature Range</b>	-30 °C to 80 °C
<b>Storage and Handling</b>	According to our care and handling instructions
<b>Compliance and Certification</b>	OEKO-TEX® STANDARD 100, Hohenstein Antibacterial Activity / Z-787074, Hohenstein Biological Safety / Z-161795, DIN EN ISO 9001:2015, REACH, RoHS, Screening test using a praxis-near carrier test system following ISO 18184:2019 against the Bovine Coronavirus

**Alterations Reserved 01.05.2021/16** – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at [www.shieldex.de](http://www.shieldex.de).

**Statex Produktions-  
und Vertriebs GmbH**  
Kleiner Ort 9-11  
28357 Bremen, Germany

**Contact**  
Tel. +49 421 27 50 47  
Fax +49 421 27 36 43  
[info@shieldex.de](mailto:info@shieldex.de)

Supplied by:  
[www.hitek-ltd.co.uk](http://www.hitek-ltd.co.uk)  
**+44 (0)1724 851678**

**HITEK**  
ELECTRONIC MATERIALS LTD

