

### PRODUCT DESCRIPTION

STYCAST FILLER SC provides the following characteristics:

<b>Technology</b>	Silica
<b>Appearance</b>	White
<b>Product Benefits</b>	<ul style="list-style-type: none"> <li>• Rheological additive in liquid polymers</li> <li>• Very fine grade solid</li> </ul>
<b>pH (4% aqueous dispersion)</b>	3.5 to 4.2
<b>Application</b>	Filler

STYCAST FILLER SC can be added to a liquid resin system to achieve a certain level of viscosity and a well defined thixotropy to avoid flowing of the product.

FILLER SC is a very fine grade solid, that is used to obtain a well defined rheology in liquid polymers.

### TYPICAL PROPERTIES OF UNCURED MATERIAL

Particle Size, average, nm	12
Ignition Loss , 1,000°C moisture-free basis, %	1
Density, g/l	2.2
Shelf Life @ 25°C, months (Minimum)	12
Flash Point , °C	7
pH (4 % aqueous dispersion)	3,5 - 4,2
Ignition loss (1000°C)	

### GENERAL INFORMATION

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

### DIRECTIONS FOR USE

1. Add desired quantity of Filler SC to the liquid resin system. Up to 5 parts by weight can be added to the resin system available.
2. Mix thoroughly.
3. Let mixture stabilise for at least 1 hour in order to get optimised properties.

### Trademark usage

Except as otherwise noted, all marks used above on this data sheet are trademarks and/or registered trademarks of Henkel and/or its affiliates in Europe and elsewhere.

Reference 0.0

### Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

### Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### Storage

Store in original, tightly covered containers in clean, dry areas. Storage information may be indicated on the product container labeling.

### Optimal Storage: 25 °C

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

<p>Supplied by:</p> <p><a href="http://www.hitek-ltd.co.uk">www.hitek-ltd.co.uk</a></p> <p>+44 (0)1724 851678</p>		<p><b>HITEK</b></p> <p>ELECTRONIC MATERIALS LTD</p>
---	--	---