

ABS-LFE


Thin flexible microwave elastomer absorber

ABS-LFE is a thin urethane absorber with magnetic loading. The absorber is designed for the suppression of surface currents and cavity resonances applications in the lower frequency range. The urethane based material is easy in bonding. For harsh environments and high temperature applications also the silicone based ABS-LFSE can be applied.

Applications :

- Lining cavities typically to suppress standing waves and surface currents.
- When bonded to a metal surface the material will reduce the reflectivity level of the metal object.
- LNB's, waveguides, amplifiers, converters and oscillators are often equipped with ABS-FLE to improve RF-stability.

Specifications :



Properties :

- Frequency range : > 1 Ghz up to 18 GHz
- Hardness : 96 Shore A
- Maximum service temperature : -40°C up to 120°C.

The information in this technical data sheet is believed by ABS Technics to be accurate and reliable. ABS Technics makes no representations or warranties of any kind on this data. All specifications can be subject to change without any notice. ABS Technics shall not be liable for incidental or consequential damages of any kind due to the usage of their material. All ABS Technics products are sold pursuant to our 'Terms and Conditions of Sale'.


Availability :

Standard outside dimensions are : 305x305x0.75mm but also specific or customized thickness, sizes and shapes can be supplied.

ABS-FLE is available in several thicknesses to suite the available space in the applications.

The urethane version assures a good and easy bonding process using self-adhesive tape.

By itself the material has very high mechanical strength and excellent abrasion resistance.



Supplied by:
www.hitek-ltd.co.uk
+44 (0)1724 851678



HITEK
ELECTRONIC MATERIALS LTD

The information in this technical data sheet is believed by ABS Technics to be accurate and reliable. ABS Technics makes no representations or warranties of any kind on this data. All specifications can be subject to change without any notice. ABS Technics shall not be liable for incidental or consequential damages of any kind due to the usage of their material. All ABS Technics products are sold pursuant to our 'Terms and Conditions of Sale'.