

Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 1 / 12

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond C Surface Activator - Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Surface activator for gluing.

1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives

Full address Niederkasseler Lohweg 18
District and Country 40547 Düsseldorf

Germany

Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure,	H336	May cause drowsiness or dizziness.
category 3		
Hazardous to the aquatic environment, chronic	H411	Toxic to aquatic life with long lasting effects.
toxicity_category 2		



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 2 / 12

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:







Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P280 Wear eye protection / face protection.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Contains: HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

INDEX $30 \le x < 60$ Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336,

Aquatic Chronic 2 H411

EC 927-510-4

CAS

FC

REACH Reg. 01-2119475515-33-XXXX

TRANS-DICHLOROETHYLENE

INDEX 602-026-00-3 $1 \le x < 5$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H336,

Aquatic Chronic 3 H412, Classification note according to Annex VI to the

CLP Regulation: C

STA Inhalation mists/powders: 1,5 mg/l

CAS 156-60-5

REACH Reg. 01-2120093504-55-XXXX

205-860-2

©EPY 11.4.1 - SDS 1004.14



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 3 / 12

SECTION 3. Composition/information on ingredients/>

N,N-DIMETHYL-p-TOLUIDINA

INDEX 612-056-00-9 0,1 ≤ x < 1 Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT RE 2 H373,

Aquatic Chronic 3 H412, Classification note according to Annex VI to the

CLP Regulation: C

EC 202-805-4 STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation

mists/powders: 0.501 mg/l

CAS 99-97-8

REACH Reg. 01-2119956633-31-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 37,50 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: inhalation of vapors can cause drowsiness and dizziness.

Eyes: it can cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor: symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 4 / 12

SECTION 6. Accidental release measures .../>>

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
FINI	Suomi	HTP_VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH

HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25

			N N DIMETH	IYL-p-TOLUID	INIA			
Predicted no-effect cor	ncentration	- PNFC	N,N-DIVIET	п Е-р-посопо	INA			
Normal value in fresh		THEO				0,153	mg/l	
Normal value in marir	ne water					0,015	mg/l	
Normal value for fres	h water sedi	ment				45,38	mg/kg	
Normal value for mar	ine water se	diment				45,38	mg/kg	
Normal value for water	er, intermitte	nt release				0,153	mg/l	
Normal value for the						18,68	mg/kg	
Health - Derived no-effe	ect level - D	NEL / DMEL						
	Effects or	n consumers			Effects on workers			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation				1.352				
				mg/m3				
Skin				1.186				
				mg/kg/d				



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 5 / 12

SECTION 8. Exposure controls/personal protection/>

				TRANS-DICHL	OROETHYLE	NE			
Threshold Limit \	/alue								
Туре	Country	untry TWA/8h STEL/15m			nin Remarks / Observations				
,,		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	800	200	1600	400				
TLV	DNK	790	200	1580	400				
HTP	FIN	800	200	1000	250				
Predicted no-effe	ct concentra	tion - PNE	3						
Normal value in	fresh water						0,0364	mg/l	
Normal value in	n marine wate	r					0,0036	mg/l	
Normal value for	or fresh water	sediment					0,548	mg/kg/d	
Normal value for	or marine wat	er sediment					0,0548	mg/kg/d	
Normal value o		•					17	mg/l	
Normal value for	or the terrestri	ial compartn	nent				0,0563	mg/kg/d	
Health - Derived r	no-effect leve	el - DNEL / I	DMEL						
	Effe	cts on consu	ımers			Effects on worke	ers		
Route of expos	ure Acut	e Acı	ıte	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	sys	temic	local	systemic	local	systemic	local	systemic
Oral					57 mg/kg bw/d				
Inhalation					198 mg/m3				797 mg/m3

		HYDROCARB	ONS, C7, N-AL	KANES, ISOAL	KANES, CYC	CLICS		
Health - Derived no-eff	ect level - D	NEL / DMEL						
	Effects or	n consumers			Effects on w			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				149				
				mg/kg bw/d				
Inhalation				447				2085
				mg/m3				mg/m3
Skin				149				300
				mg/kg bw/d				mg/kg
								bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type A filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 6 / 12

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance aerosol Colour colourless Odour solvent Melting point / freezing point not available Initial boiling point 78 °C Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point -26 °C not available Auto-ignition temperature Decomposition temperature not available not available Kinematic viscosity not available Dynamic viscosity ~0.7 mPa s Solubility not available Partition coefficient: n-octanol/water not available Vapour pressure not available Density and/or relative density 0,7 Relative vapour density not available Particle characteristics not applicable

Information

Reason for missing data:substance/mixture not

stable

Temperature: 23 °C

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

The reactions with the following materials can generate heat: cyanacrililated stickers

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

In normal use and storage conditions, no dangerous reactions are predictable.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing and oxidants, strong bases and acids, high temperature materials.

10.6. Hazardous decomposition products

For thermal decomposition, carbon monoxide, carbon dioxide and Other unidentified organic compounds.



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 7 / 12

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Inhalation: gas or vapors in high concentrations can irritate the respiratory tract. Vapors can

cause headache, exhaustion, dizziness and nausea.

Contact with the skin: the effect of the product on the skin is of loss of skin fat. The repeated exposure can

cause dryness and chapping of the skin.

Contact with eyes: irritating and can cause redness and pain.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l
ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: >2000 mg/kg

N,N-DIMETHYL-p-TOLUIDINA

LD50 (Dermal): > 2000 mg/kg

STA (Dermal): 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 1767 mg/kg

STA (Oral): 100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LC50 (Inhalation vapours): 1,4 mg/l/4h STA (Inhalation mists/powders): 0,501 mg/l

(figure used for calculation of the acute toxicity estimate of the mixture)

TRANS-DICHLOROETHYLENE

 LD50 (Dermal):
 > 5000 mg/kg

 LD50 (Oral):
 7902 mg/kg

 LC50 (Inhalation vapours):
 24100 ppm/4h

 STA (Inhalation mists/powders):
 1,5 mg/l

(figure used for calculation of the acute toxicity estimate of the mixture)

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS LD50 (Dermal): 3000 mg/kg LD50 (Oral): > 8 mg/kg LC50 (Inhalation vapours): > 23,3 mg/l/4h

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 8 / 12

SECTION 11. Toxicological information .../>>

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment

12.1. Toxicity

N,N-DIMETHYL-p-TOLUIDINA

LC50 - for Fish 52 mg/l/96h

TRANS-DICHLOROETHYLENE

LC50 - for Fish 135 mg/l/96h EC50 - for Crustacea 250 mg/l/48h

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

 LC50 - for Fish
 > 13,4 mg/l/96h

 EC50 - for Crustacea
 3 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 20 mg/l/72h

12.2. Persistence and degradability

TRANS-DICHLOROETHYLENE

NOT rapidly degradable

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

E١



Permabond Engineering Adhesives

Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 9 / 12

SECTION 12. Ecological information/>>

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class: 16 05 04 gas in pressure containers, containing dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: -- Limited Quantities: 1 L Tunnel restriction code: (D)

Special provision: 190, 327, 344, 625

IMDG: EMS: F-D, S-U Limited Quantities: 1 L

IATA: Cargo: Maximum quantity: 150 Kg

Cargo: Maximum quantity: 150 Kg Packaging instructions: 203
Pass.: Maximum quantity: 75 Kg Packaging instructions: 203

Special provision: A145, A167, A802

©EPY 11.4.1 - SDS 1004.14

E١



Permabond Engineering Adhesives

Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 10 / 12

SECTION 14. Transport information .../>>

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Aerosol 1
Aerosol, category 1
Aerosol 3
Aerosol, category 3
Flam. Liq. 2
Acute Tox. 3
Acute Tox. 4
Asp. Tox. 1
Aerosol, category 3
Acute toxicity, category 3
Acute toxicity, category 4
Asp. Tox. 1
Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

E١



Permabond Engineering Adhesives

Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 11 / 12

SECTION 16. Other information .../>>

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website



Permabond C Surface Activator - Aerosol

Revision nr.1 Dated 06/03/2023 First compilation Printed on 06/03/2023 Page n. 12 / 12

SECTION 16. Other information .../>>

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.