

SAFETY DATA SHEET Permabond ET5011B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond ET5011B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesTwo-component, epoxy-based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives GmbH

Niederkasseler Lohweg 18

40547 Düsseldorf

Germany

info.europe@permabond.com

Manufacturer Permabond Engineering Adhesives Ltd.

Wessex Way Colden Common Winchester

Hampshire SO21 1WP United Kingdom

Tel: +44 (0)1962 711 661 Fax: +44 (0)1962 711 662 info@permabond.co.uk

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone CHEMTREC Ireland: +(353)-19014670 number CHEMTREC Australia: +(61)-290372994

CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aguatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms





Signal word Danger

Permabond ET5011B

Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352a IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

Contains MERCAPTAN-TERMINATED OLIGOMER, 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL,

BIS[(DIMETHYLAMINO)METHYL]PHENOL

Supplementary precautionary

statements

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with existing Community, National and

local regulations.

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

MERCAPTAN-TERMINATED OLIGOMER	60-100%
MERCAPTAN-TERMINATED OLIGOMER	60-100%

CAS number: 72244-98-5 EC number: 701-196-7 REACH registration number: 01-

2120118957-46-XXXX

Classification

Skin Sens. 1B - H317 Aquatic Chronic 3 - H412

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL 5-10%

CAS number: 90-72-2 EC number: 202-013-9 REACH registration number: 01-

2119560597-27-XXXX

Classification

Skin Corr. 1A - H314

2-ETHYLHEXANOIC ACID 1-5%

CAS number: 149-57-5 EC number: 205-743-6 REACH registration number: 01-

2119488942-23-XXXX

Classification

Repr. 2 - H361d

Permabond ET5011B

BIS[(DIMETHYLAMINO)METHYL]PHENOL

1-5%

CAS number: 71074-89-0 EC number: 275-162-0

IMPURITY

Classification

Skin Corr. 1B - H314 Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move the exposed person to fresh air. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water.

Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. If symptoms

develop, obtain medical attention

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any

contact lenses and open eyelids wide apart. Get medical attention. Show this Safety Data

Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Ingestion May cause chemical burns in mouth and throat.

Skin contact Chemical burns. Mild dermatitis, allergic skin rash.

Eye contact May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NOx). Carbon

products monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

for firefighters clothin

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsWear protective clothing as described in Section 8 of this safety data sheet.

Permabond ET5011B

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for

disposal. Wash area with soap and water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when

using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Corrosive storage.

7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

MERCAPTAN-TERMINATED OLIGOMER (CAS: 72244-98-5)

DMEL Workers - Inhalation; Long term systemic effects: 22 mg/m³

Workers - Dermal; Long term systemic effects: 2.7 mg/kg/day

PNEC Fresh water; 70 μg/l

marine water; 7 μg/l

STP; 10 mg/l

Sediment (Freshwater); 322 µg/kg, dw Sediment (Marinewater); 32 µg/kg, dw

Soil; 23 µg/kg, dw

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (CAS: 90-72-2)

PNEC Fresh water; 0.084 mg/l

marine water; 0.008 mg/l

STP; 0.2 mg/l

2-ETHYLHEXANOIC ACID (CAS: 149-57-5)

DNEL Workers - Inhalation; Long term systemic effects: 14 mg/cm²

Workers - Dermal; Long term systemic effects: 2 mg/kg/day

PNEC Fresh water; 0.36 mg/l

marine water; 0.036 mg/l

STP; 71.7 mg/l

Sediment (Freshwater); 6.37 mg/kg Sediment (Marinewater); 0.637 mg/kg

Permabond ET5011B

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

Respiratory protection

Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

Odour Characteristic.

Odour threshold Not determined.

pH Not determined.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point >100°C

Evaporation rate Not available.

Upper/lower flammability or

explosive limits

Not available.

Vapour pressure Not determined.

Permabond ET5011B

Vapour density Not determined.

Relative density 1.1

Solubility(ies) Insoluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient Not available.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity ≈17000 mPa s @ 23°C

Explosive properties Not determined.

Oxidising properties Not applicable.

9.2. Other information

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Under normal conditions of storage and use, no hazardous reactions will occur.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Reactions with the following materials may generate heat: Epoxy resin

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified

organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Permabond ET5011B

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature. In high concentrations, vapours may irritate throat and respiratory

system and cause coughing.

Ingestion Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or

vomiting.

Skin contact This product is strongly irritating. Prolonged contact may cause burns.

Eye contact Causes serious eye damage.

Toxicological information on ingredients.

MERCAPTAN-TERMINATED OLIGOMER

Acute toxicity - oral

Acute toxicity oral (LD50

2,600.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 10,200.0

mg/kg)

Species Rabbit

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Not irritating.

Serious eye damage/irritation

Serious eye

Method: OECD 405, Rabbit Not irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity -

No information available.

fertility

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

Acute toxicity - oral

Permabond ET5011B

Acute toxicity oral (LD50

mg/kg)

2,169.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 1,280.0

mg/kg)

Species Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Corrosive.

Serious eye damage/irritation

Serious eye Irritating to eyes. Risk of serious damage to eyes.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity -

Screening - NOAEL 15 mg/kg/day, Oral, Rat F1

fertility

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: >150 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Not available.

2-ETHYLHEXANOIC ACID

Acute toxicity - oral

Acute toxicity oral (LD50

3,000.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 1,142.0

mg/kg)

Permabond ET5011B

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Moderately irritating.

Serious eye damage/irritation

Serious eye Method: OECD 405, Rabbit Not irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity -

Screening - NOAEL 3845 mg/kg, Oral, Rat F1

fertility

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: 250 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Not available.

SECTION 12: Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. Do not empty into drains.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

MERCAPTAN-TERMINATED OLIGOMER

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 87 mg/l, Danio rerio (Zebrafish)

Permabond ET5011B

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 12 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: >733 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms

EC₅o, 3 hours:

EC₅₀, 3 hours: > 1000 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 3.5 mg/l, Daphnia magna

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

Acute aquatic toxicity

Acute toxicity - fish LC₈₀, 96 hours: > 180 - < 240 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

LC₅o, 96 hours: 718 mg/l, Palaemonetes vulgaris

Acute toxicity - aquatic

plants

EC₅o, 72 hours: 84 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms

NOEC, 28 days: 2 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

Biodegradation Water - 4%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local

regulations Empty containers may contain product residue; follow SDS and label warnings

even after they have been emptied.

Permabond ET5011B

Disposal methodsDo not empty into drains, dispose of this material and its container at hazardous or special

waste collection point.

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances.

SECTION 14: Transport information

14.1. UN number

2735

14.2. UN proper shipping name

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (contains 2,4,6-Tris(dimethylaminomethyl)phenol)

14.3. Transport hazard class(es)

8

Transport labels



14.4. Packing group

Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH)

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

Permabond ET5011B

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 27/01/2022

Revision 5

Supersedes date 04/04/2019

Hazard statements in full H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.