

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Permabond 4UV80HV**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses	Industrial	Professional	Consumer
Use	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives**
Full address **Niederkasseler Lohweg 18**
District and Country **40547 Düsseldorf Germany**
Tel. **+44 (0)1962 711 661**
e-mail address of the competent person responsible for the Safety Data Sheet **info.europe@permabond.com**
Supplier: **Permabond Engineering Adhesives Ltd**
Wessex Way, Colden Common,
Winchester, Hampshire SO21 1WP, UK
tel: **+44 (0)1962 711 661**
mail: **info.europe@permabond.com**

1.4. Emergency telephone number

For urgent inquiries refer to **+44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)**

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 1B	H360D	May damage the unborn child.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H360D	May damage the unborn child.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.
	Restricted to professional users.

Precautionary statements:

P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.

Contains:

TETRAHYDROFURFURYL METHACRYLATE
ISOBORNYL ACRYLATE
DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE
2-PROPENOIC ACID, HOMOPOLYMER

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ISOBORNYL ACRYLATE		
INDEX	$30 \leq x < 60$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	227-561-6	
CAS	5888-33-5	
REACH Reg.	01-2119957862-25-XXXX	
TETRAHYDROFURFURYL METHACRYLATE		
INDEX	$5 \leq x < 10$	Repr. 1B H360D, Skin Sens. 1 H317, Aquatic Chronic 3 H412
EC	219-529-5	
CAS	2455-24-5	
REACH Reg.	1-2120748481-53-XXXX	

SECTION 3. Composition/information on ingredients ... / >>

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

INDEX $2,5 \leq x < 3$

Repr. 2 H361f, Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 278-355-8

CAS 75980-60-8

REACH Reg. 01-2119972295-29-XXXX

2-PROPENOIC ACID, HOMOPOLYMER

INDEX $2,5 \leq x < 3$

Acute Tox. 4 H302, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 618-347-7

CAS 9003-01-4

REACH Reg. 01-2120754771-50-XXXX

LD50 Oral: 1500 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Give plenty of water to drink. Do not cause vomiting. Consult a doctor.

Inhalation: Move the exposed person to fresh air. Consult a doctor in case of serious symptoms or persistent.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash.

Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO₂), and nitric oxides (NO_x).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Permabond®

Engineering Adhesives

Permabond Engineering Adhesives

Permabond 4UV80HV

Revision nr.2

Dated 30/01/2024

Printed on 30/01/2024

Page n. 4 / 12

Replaced revision:1 (Dated 18/07/2023)

EN

SECTION 6. Accidental release measures ... / >>

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1C

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

ISOBORNYL ACRYLATE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,00092	mg/l			
Normal value in marine water				0,00009	mg/l			
				2				
Normal value for fresh water sediment				0,145	mg/kg			
Normal value for marine water sediment				0,0145	mg/kg			
Normal value of STP microorganisms				2	mg/l			
Normal value for the terrestrial compartment				0,0285	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0.83				
				mg/kg bw/d				
Skin				0.83				1.39
				mg/kg bw/d				mg/kg bw/d

EPY 11.5.2 - SDS 1004.14

SECTION 8. Exposure controls/personal protection ... / >>

2-PROPENOIC ACID, HOMOPOLYMER

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,003	mg/l
Normal value for fresh water sediment	0,021	mg/kg
Normal value for marine water sediment	0,002	mg/kg
Normal value for water, intermittent release	0,001	mg/l
Normal value of STP microorganisms	0,9	mg/l
Normal value for the food chain (secondary poisoning)	0,003	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,2 mg/kg bw/d				
Inhalation				0,348 mg/m3				1,97 mg/m3
Skin				0,2 mg/kg bw/d		0,56 mg/kg bw/d		

TETRAHYDROFURFURYL METHACRYLATE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,347	mg/l
Normal value in marine water	0,035	mg/l
Normal value for fresh water sediment	2,12	mg/kg/d
Normal value for marine water sediment	0,212	mg/kg/d
Normal value of STP microorganisms	15,8	mg/l
Normal value for the terrestrial compartment	0,221	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,5 mg/kg/d				
Inhalation				0,87 mg/m3				3,53 mg/m3
Skin				0,5 mg/kg/d				1 mg/kg/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an

SECTION 8. Exposure controls/personal protection ... / >>

emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	opalescent	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 100 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	not available	
Dynamic viscosity	~ 2300 mPa.s	Temperature: 23 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,1	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Strong oxidizing agents, Reducing agents, strong acids and bases.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

SECTION 10. Stability and reactivity ... / >>

See the reactivity section.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

ISOBORNYL ACRYLATE

LD50 (Dermal):	> 3000 mg/kg
LD50 (Oral):	4350 mg/kg

2-PROPENOIC ACID, HOMOPOLYMER

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	1500 mg/kg
LC50 (Inhalation vapours):	> 5,1 mg/l/4h

TETRAHYDROFURFURYL METHACRYLATE

LD50 (Oral):	3945 mg/kg
--------------	------------

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 5000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

ISOBORNYL ACRYLATE

LC50 - for Fish	0,704 mg/l/96h
EC50 - for Algae / Aquatic Plants	1,98 mg/l/72h
Chronic NOEC for Fish	0,431 mg/l
Chronic NOEC for Crustacea	0,092 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,405 mg/l

2-PROPENOIC ACID, HOMOPOLYMER

LC50 - for Fish	27 mg/l/96h
EC50 - for Crustacea	47 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,13 mg/l/72h
EC10 for Algae / Aquatic Plants	0,03 mg/l/72h

TETRAHYDROFURFURYL METHACRYLATE

LC50 - for Fish	34,7 mg/l/96h
EC50 - for Crustacea	69 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	9,4 mg/l
Chronic NOEC for Crustacea	37,2 mg/l

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

LC50 - for Fish	6,53 mg/l/96h 48h
EC50 - for Crustacea	3,53 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 2,01 mg/l/72h
EC10 for Algae / Aquatic Plants	1,56 mg/l/72h

12.2. Persistence and degradability

ISOBORNYL ACRYLATE

NOT rapidly degradable

SECTION 12. Ecological information ... / >>

TETRAHYDROFURFURYL METHACRYLATE
NOT rapidly degradable

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE
NOT rapidly degradable

12.3. Bioaccumulative potential

TETRAHYDROFURFURYL METHACRYLATE
Partition coefficient: n-octanol/water 1,38 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity $\leq$ 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity $\leq$ 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity $\leq$ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; 2-PROPENOIC ACID, HOMOPOLYMER)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; 2-PROPENOIC ACID, HOMOPOLYMER)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE; 2-PROPENOIC ACID, HOMOPOLYMER)

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
	Special provision: -		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE
REACH Reg.: 01-2119972295-29-XXXX

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

SECTION 15. Regulatory information ... / >>

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)
WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 1B	Reproductive toxicity, category 1B
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H360D	May damage the unborn child.
H361f	Suspected of damaging fertility.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

SECTION 16. Other information ... / >>

- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 03.