

Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 1 / 12 Replaced revision:1 (Dated 03/07/2023)

Permabond TA4210B

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1 Identification of the s	substance/mixture and of the company/undertaking
	substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Permabond TA4210B
1.2. Relevant identified uses of the substance	or mixture and uses advised against
Intended use	Adhesive
1.3. Details of the supplier of the safety data s	heet
Name Full address District and Country	Permabond Engineering Adhesives Niederkasseler Lohweg 18 40547 Düsseldorf Germany
e-mail address of the competent person responsible for the Safety Data Sheet	Tel. +44 (0)1962 711 661 info.europe@permabond.com
Supplier:	Permabond Engineering Adhesives Ltd Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK tel: +44 (0)1962 711 661 mail: info.europe@permabond.com
1.4. Emergency telephone number	
For urgent inquiries refer to	+44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)
	CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 2 / 12 Replaced revision:1 (Dated 03/07/2023)

Permabond TA4210B

SECTION 2. Hazards identification/>>

Signal words:	Warning
Hazard statements:	
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
Precautionary statements:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
Container	
Contains:	
	2-HYDROXYETHYL METHACRYLATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
METHYLMETH	ACRYLATE		
INDEX		30 ≤ x < 60	Flam. Liq. 2 H225, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317
EC	201-297-1		
CAS	80-62-6		
REACH Reg.	01-2119452498-28	-XXXX	
2-HYDROXYE	THYL METHACRYL	ATE	
INDEX		10 ≤ x < 30	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317
EC	212-782-2		
CAS	868-77-9		
REACH Reg.	01-2119490169-29	-XXXX	
3,5-DIETHYL-	1,2-DIHYDRO-1-PHE	NYL-2-PROPYLPYRID	INE
INDEX		1≤x< 5	Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Chronic 4
			H413
EC	252-091-3		LD50 Oral: >500 mg/kg
CAS	34562-31-7		
REACH Reg.	01-2120769712-47	-XXXX	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash Readyly and abundantly the eyes with water keeping the eyelids open. Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues. Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink. Do not cause vomiting. Consult a doctor.

@EPY 11.5.1 - SDS 1004.14

Permabond TA4210B

SECTION 4. First aid measures ... / >>

Permabond

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or persistent.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



Permabond TA4210B

Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 4 / 12 Replaced revision:1 (Dated 03/07/2023)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

3

Storage class TRGS 510 (Germany):

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

5-11		
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH
		HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki
	3, 3	tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības
		prasības saskarē ar kīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i
Non	Norge	arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og
		grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	5 /· 5
NLD	Neuenanu	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3,
DOI	Dalaha	eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające
		rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych
		dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru
		modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska
		gränsvärden (AFS 2018:1)



.

Permabond TA4210B

SECTION 8. Exposure controls/personal protection ... / >>

2-HYDROXYETHYL METHACRYLATE

			2-1						
hreshold Limit Value									
Туре Со	untry T	WA/8h		STEL/15	min	Remarks	Observations		
	m	ıg/m3	ppm	mg/m3	ppm				
TLV NO	R	11	2	11	2				
Predicted no-effect co	ncentration	n - PNEC							
Normal value in fresh	n water						0,482	mg/l	
Normal value in mari	ne water						0,0482	mg/l	
Normal value for fres	h water seo	diment					3,79	mg/kg	
Normal value for mar	ine water s	ediment					3,79	mg/kg	
Normal value for fres	h water, int	ermittent	release				1	mg/l	
Normal value of STP	microorgan	nisms					10	mg/l	
Normal value for the	terrestrial c	ompartme	ent				0,476	mg/kg	
lealth - Derived no-eff	ect level -	DNEL / D	MEL						
	Effects of	on consun	ners			Effects on w	vorkers		
Route of exposure	Acute	Acut	е	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	syste	emic	local	systemic	local	systemic	local	systemic
Oral					0.83				0.83
					mg/kg/d				mg/kg/d
Inhalation					2.9				4.9
					mg/m3				mg/m3
Skin					0.83				1.3
					mg/kg/d				mg/kg/d

METHYLMETHACRYLATE

Threshold Limit V	/alue								
Туре	Country	TWA/8h		STEL/15	min	Remarks /	Observations		
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	210	50	420	100				
TLV	DNK	102	25	204	50				
VLA	ESP	100	50	416	100				
VLEP	FRA	205	50	410	100				
HTP	FIN	42	10	210	50				
AK	HUN	208		415					
VLEP	ITA		50		100				
RV	LVA	10							
TLV	NOR	100	25	400	100				
TGG	NLD	205		410					
NDS/NDSCh	POL	100		300					
TLV	ROU	205	50	410	100				
NGV/KGV	SWE	200	50	400	100				
Predicted no-effe	ct concentr	ation - PNE	C						
Normal value ir	n fresh water						0,94	mg/l	
Normal value ir	n marine wat	er					0,094	mg/l	
Normal value for	or fresh wate	r sediment					10,2	mg/kg	
Normal value o	f STP micro	organisms					10	mg/l	
Normal value for	or the terrest	rial compartr	nent				1,48	mg/kg	
Health - Derived r	no-effect lev	/el - DNEL /	DMEL					0 0	
	Effe	ects on consu	umers			Effects on w	/orkers		
Route of expos	ure Acu	ite Aci	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	al sys	temic	local	systemic	local	systemic	local	systemic
Oral					8,2				
					mg/kg/d				
Inhalation		208	3		74,3		416		208
		mg	/m3		mg/m3		mg/m3		mg/m3
Skin					8,2		0,0015		13,7
					mg/kg/d		mg/cm2		mg/kg/d
							-		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.



Permabond TA4210B

SECTION 8. Exposure controls/personal protection ... / >>

Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station. HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	
Appearance	liquid	
Colour	white	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	100 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	30 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Dynamic viscosity	~ 45000 mPa.s	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1	
Relative vapour density	not available	
Particle characteristics	not applicable	

Information

Reason for missing data:substance/mixture is non-soluble (in water)

Temperature: 25 °C

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available



Permabond TA4210B

FN

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture: Not classified (no significant component) >2000 mg/kg Not classified (no significant component)

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE						
LD50 (Dermal): > 1000 r						
LD50 (Oral):	> 500 mg/kg					

2-HYDROXYETHYL METHACRYLATE LD50 (Dermal): LD50 (Oral):

METHYLMETHACRYLATE LD50 (Dermal):

> 5000 mg/kg

> 5000 mg/kg

> 5000 mg/kg

@EPY 11.5.1 - SDS 1004.14



Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 8 / 12 Replaced revision:1 (Dated 03/07/2023)

Permabond TA4210B

SECTION 11. Toxicological information/>>

LD50 (Oral): LC50 (Inhalation vapours): > 5000 mg/kg 29,8 mg/l/4h

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYI EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Algae / Aquatic Plants	RIDINE 22 mg/l/48h 40 mg/l/72h 16 mg/l
2-HYDROXYETHYL METHACRYLATE LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants	> 100 mg/l/96h 380 mg/l/48h 836 mg/l/72h
METHYLMETHACRYLATE LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l/96h 69 mg/l/48h > 100 mg/l/72h 9,4 mg/l 37 mg/l > 110 mg/l

EN

Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 9 / 12 Replaced revision:1 (Dated 03/07/2023)

Permabond TA4210B

SECTION 12. Ecological information ... / >>

12.2. Persistence and degradability

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE NOT rapidly degradable

2-HYDROXYETHYL METHACRYLATE Rapidly degradable

METHYLMETHACRYLATE Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1993

14.2. UN proper shipping name

ADR / RID:	FLAMMABLE LIQUID, N.O.S.
IMDG:	FLAMMABLE LIQUID, N.O.S.
IATA:	FLAMMABLE LIQUID, N.O.S.

Permabond[®]

Permabond Engineering Adhesives

Permabond TA4210B

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3	
IMDG:	Class: 3	Label: 3	
IATA:	Class: 3	Label: 3	

14.4. Packing group

ADR / RID, IMDG, IATA: Ш

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:

IMDG: ΙΑΤΑ·

Special provision: 274, 601 EMS: F-E, <u>S-E</u> Cargo: Passengers: Special provision:

HIN - Kemler: 30

Limited Quantities: 5 L

Limited Quantities: 5 L Maximum quantity: 220 L Maximum quantity: 60 L A3

Tunnel restriction code: (D/E)

Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product Point 3 - 40

P5c

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



Permabond TA4210B

SECTION 15. Regulatory information ... / >>

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017) WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).
- GENERAL BIBLIOGRAPHY
- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament



Revision nr.2 Dated 03/07/2023 Printed on 03/07/2023 Page n. 12 / 12 Replaced revision:1 (Dated 03/07/2023)

Permabond TA4210B

SECTION 16. Other information ... / >>

- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified: 01.