

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond UV620

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond UV620

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives GmbH
Niederkasseler Lohweg 18
40547 Düsseldorf
Germany
info.europe@permabond.com

Manufacturer Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info@permabond.co.uk

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone number CHEMTREC UK: +(44)-870-8200418
CHEMTREC US: 800-424-9300
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word Warning

Permabond UV620

Hazard statements	H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352a IF ON SKIN: Wash with plenty of soap and water P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/ attention.
Contains	2-HYDROXYETHYL METHACRYLATE, ISOBORNYL ACRYLATE, ACRYLIC ACID, DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with existing Community, National and local regulations.

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-HYDROXYETHYL METHACRYLATE	10-30%
CAS number: 868-77-9	EC number: 212-782-2
	REACH registration number: 01-2119490169-29-XXXX
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	

Permabond UV620

ISOBORNYL ACRYLATE			10-30%
CAS number: 5888-33-5	EC number: 227-561-6	REACH registration number: 01-2119957862-25-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		
Classification			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Skin Sens. 1 - H317			
STOT SE 3 - H335			
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			
ACRYLIC ACID			1-3%
CAS number: 79-10-7	EC number: 201-177-9	REACH registration number: 01-2119452449-31-XXXX	
M factor (Acute) = 1			
Classification			
Flam. Liq. 3 - H226			
Acute Tox. 4 - H302			
Acute Tox. 4 - H312			
Acute Tox. 4 - H332			
Skin Corr. 1A - H314			
Eye Dam. 1 - H318			
STOT SE 3 - H335			
Aquatic Acute 1 - H400			
Aquatic Chronic 2 - H411			
DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE			1-<3%
CAS number: 75980-60-8	EC number: 278-355-8	REACH registration number: 01-2119972295-29-XXXX	
Classification			
Skin Sens. 1B - H317			
Repr. 2 - H361f			
Aquatic Chronic 2 - H411			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms develop, obtain medical attention

Permabond UV620

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause respiratory system irritation.

Skin contact Skin irritation. Mild dermatitis, allergic skin rash.

Eye contact Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use in a well ventilated area. Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Protect against direct sunlight. Never return unused material to storage receptacle.

7.3. Specific end use(s)

Specific end use(s) Adhesive.

Permabond UV620

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)

DNEL Workers, Industry - Inhalation; Long term systemic effects: 4.9 mg/m³
Workers, Industry - Dermal; Long term systemic effects: 1.3 mg/kg/day

PNEC Workers, Industry - Water; Long term 0.482 mg/l
Workers, Industry - Soil; Long term 0.476 mg/kg
Workers, Industry - STP; Long term 10 mg/l
Workers, Industry - Fresh water; 3.79 mg/kg

ISOBORNYL ACRYLATE (CAS: 5888-33-5)

DNEL Workers - Dermal; Long term systemic effects: 1.39 mg/kg/day

PNEC Fresh water; 0.001 mg/l
marine water; 0 mg/l
STP; 2 mg/l
Sediment (Freshwater); 0.145 mg/kg
Sediment (Marinewater); 0.015 mg/kg

ACRYLIC ACID (CAS: 79-10-7)

DNEL Workers - Inhalation; Long term local effects: 30 mg/m³
Workers - Dermal; Short term local effects: 1 mg/cm²

PNEC Fresh water; 0.003 mg/l
Intermittent release; 0.001 mg/l
marine water; 0 mg/l
STP; 0.9 mg/l
Sediment (Freshwater); 0.024 mg/kg/day
Sediment (Marinewater); 0.002 mg/kg/day

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE (CAS: 75980-60-8)

DNEL Workers - Inhalation; Long term systemic effects: 3.5 mg/m³
Workers - Dermal; Long term systemic effects: 1 mg/kg/day

PNEC Fresh water; 0.004 mg/l
marine water; 0 mg/l
Sediment (Freshwater); 0.29 mg/kg
Sediment (Marinewater); 0.029 mg/kg
Soil; 0.056 mg/kg
STP; >1000 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Permabond UV620

Eye/face protection	The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166
Hand protection	It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
Other skin and body protection	Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.
Respiratory protection	Ensure adequate ventilation of the working area. Not available. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Acrylic
Odour threshold	Not available.
pH	Not relevant.
Melting point	Not available.
Initial boiling point and range	Not applicable.
Flash point	$>100^{\circ}\text{C}$
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.0
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Viscosity	≈ 2500 mPa s @ 23°C

Permabond UV620

Oxidising properties Not available.

9.2. Other information

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Strong oxidising agents.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions There are no known reactivity hazards associated with this product.

10.4. Conditions to avoid

Conditions to avoid Protect against direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong reducing agents. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation

May cause respiratory system irritation.

Skin contact

Irritating to skin.

Eye contact

Irritating to eyes.

Toxicological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Permabond UV620

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 5,000.0
mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Animal data Erythema/eschar score: Very slight erythema - barely perceptible (1). Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Conclusive data but not sufficient for classification.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL \geq 1000 mg/kg/day, Oral, Rat F1

Reproductive toxicity - development Developmental toxicity: - NOAEL: \geq 1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard Not applicable.

ISOBORNYL ACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 5,000.0
mg/kg)

Species Rat

Acute toxicity - dermal

Permabond UV620

Acute toxicity dermal (LD₅₀ 3,000.0 mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - : Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Genome mutation: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOEC 0.092 mg/l, Inhalation, Rat P

Reproductive toxicity - development Developmental toxicity: - NOAEL: 500 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

ACRYLIC ACID

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 1,405.0 mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0 mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 3.6

Permabond UV620

Species	Rat
<u>Skin corrosion/irritation</u>	
Animal data	Rabbit Highly corrosive.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Rabbit Corrosive
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative.
Genotoxicity - in vivo	Chromosome aberration: Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEL \geq 78 mg/kg/day, Oral, Rat
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	- NOAEL 460 mg/l, Oral, Rat P, F1
Reproductive toxicity - development	Fetotoxicity: - NOAEC: \geq 0.673 mg/l, Inhalation, Rabbit
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No information available.
<u>Aspiration hazard</u>	
Aspiration hazard	Not available.

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.1
Species	Rat
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	No information available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.

Permabond UV620

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Carcinogenicity

Carcinogenicity No data available.

Reproductive toxicity

Reproductive toxicity - fertility Possible risk of adverse reproductive effects.

Reproductive toxicity - development Developmental toxicity: - NOEL: 150 mg/kg, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOEL 50 mg/kg/day, Oral, Rat

Aspiration hazard

Aspiration hazard No data available.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 100 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 380 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 836 mg/l, Selenastrum capricornutum
NOEC, 72 hours: 400 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₅₀, 16 hours: > 3000 mg/l, Pseudomonas fluorescens

Chronic aquatic toxicity

Permabond UV620

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 24.1 mg/l, Daphnia magna

ISOBORNYL ACRYLATE

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 0.704 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic plants EC₅₀, 72 hours: 1.98 mg/l, Pseudokirchneriella subcapitata
NOEC, 72 hours: 0.405 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

M factor (Chronic) 1

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.092 mg/l, Daphnia magna

ACRYLIC ACID

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 222 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: 270 mg/l, Daphnia magna
EC₅₀, 48 hours: 95 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 0.04 mg/l, Desmodosmus subspicatus
EC₅₀, 96 hours: 0.17 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC₂₀, 30 minutes: 900 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 19 mg/l, Daphnia magna

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: 6.53 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.53 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: > 2.01 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC₅₀, 180 minutes: > 1000 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability No data available.

Permabond UV620

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Biodegradation Water - Degradation 84%: 28 days

ISOBORNYL ACRYLATE

Biodegradation Water - Degradation 57%: 28 days

ACRYLIC ACID

Biodegradation Water - Degradation 81%: 28 days

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Biodegradation Water - Degradation < 20%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Bioaccumulative potential BCF: 1.34 - 1.54,

ACRYLIC ACID

Partition coefficient log Kow: 0.46

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Bioaccumulative potential BCF: 23 - 55, Cyprinus carpio (Common carp)

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Adsorption/desorption coefficient Water - Koc: 42.7 @ 20°C

ACRYLIC ACID

Surface tension 69.6 mN/m @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

Permabond UV620

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

Road transport notes	Applies only to inner containers >5 litres. See SP 375
Sea transport notes	Applies only to inner containers >5 litres. See 2.10.2.7 of the IMDG code.
Air transport notes	Applies only to inner containers >5 litres. See SP A197 (375)

14.1. UN number

3082

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Isobornyl Acrylate)

14.3. Transport hazard class(es)

9

Transport labels



14.4. Packing group

III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
-----------------------------	---

Permabond UV620

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	02/11/2021
Revision	6
Supersedes date	03/07/2018
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H361f Suspected of damaging fertility. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.