

Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 1 / 13

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond UV640

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive

Identified Uses Industrial Professional Consumer
Use -

1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives
Full address Niederkasseler Lohweg 18
District and Country 40547 Düsseldorf
Germany

Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| Reproductive toxicity, category 1B | H360D | May damage the unborn child. |
|---|-------|--|
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Hazardous to the aquatic environment, chronic | H411 | Toxic to aquatic life with long lasting effects. |
| toxicity, category 2 | | |
| | | |



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 2 / 13

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H360D May damage the unborn child.
H318 Causes serious eye damage.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H411 Toxic to aquatic life with long lasting effects.

Restricted to professional users.

Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.

Contains: TETRAHYDROFURFURYL METHACRYLATE

N,N-DIMETHYLACRYLAMIDE

2-HYDROXYETHYL METHACRYLATE

 ${\sf DIPHENYL} (2,4,6\text{-}{\sf TRIMETHYLBENZOYL}) {\sf PHOSPHINE\ OXIDE\ }$

ISOBORNYL ACRYLATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

TETRAHYDROFURFURYL METHACRYLATE

INDEX 10 ≤ x < 25 Repr. 1B H360D, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 219-529-5 CAS 2455-24-5

REACH Reg. 1-2120748481-53-XXXX

ISOBORNYL ACRYLATE

INDEX 10 ≤ x < 20 **Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317,**

Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 227-561-6 CAS 5888-33-5

REACH Reg. 01-2119957862-25-XXXX

EPY 11.5.1 - SDS 1004.14



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 3 / 13

SECTION 3. Composition/information on ingredients

N,N-DIMETHYLACRYLAMIDE

INDEX 10 ≤ x < 14 Acute Tox. 3 H301, Acute Tox. 3 H311, Eye Dam. 1 H318

EC 220-237-5 LD50 Oral: 280 mg/kg, LD50 Dermal: 720 mg/kg

CAS 2680-03-7

REACH Reg. 01-2119971262-39-XXXX 2-HYDROXYETHYL METHACRYLATE

INDEX 5 ≤ x < 10 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 212-782-2 CAS 868-77-9

REACH Reg. 01-2119490169-29-XXXX

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

INDEX 2,5 ≤ x < 3 Repr. 2 H361f, Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 278-355-8 CAS 75980-60-8

REACH Reg. 01-2119972295-29-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request

medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash

Readyly and abundantly the eyes with water keeping the eyelids open.

Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink.

Do not cause vomiting. Consult a doctor.

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or persistent.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 4 / 13

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1C

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

NOR Norge Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i

arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og

grenseverdier), 21. august 2018 nr. 1255



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 5 / 13

SECTION 8. Exposure controls/personal protection

| | | | 2-l | iydroxyeth | YL METHACF | RYLATE | | | |
|--|--------------|--------------|-----------|------------|------------|--------------|--------------------|---------|----------|
| reshold Limit Va | lue | | | | | | | | |
| Туре | Country | TWA/8h | | STEL/15 | STEL/15min | | Observations | | |
| | | mg/m3 | ppm | mg/m3 | ppm | | | | |
| TLV | NOR | 11 | 2 | 11 | 2 | | | | |
| redicted no-effect | concentrat | ion - PNEC | ; | | | | | | |
| Normal value in f | resh water | | | | | | 0,482 | mg/l | |
| Normal value in r | narine water | | | | | | 0,0482 | mg/l | |
| Normal value for | fresh water | sediment | | | | | 3,79 | mg/kg | |
| Normal value for | marine wate | r sediment | | | | | 3,79 | mg/kg | |
| Normal value for | fresh water, | intermittent | t release | | | | 1 | mg/l | |
| Normal value of S | STP microor | ganisms | | | | | 10 | mg/l | |
| Normal value for the terrestrial compartment | | | | | | | 0,476 | mg/kg | |
| lealth - Derived no | -effect leve | I - DNEL / [| OMEL | | | | | | |
| | Effect | ts on consu | mers | | | Effects on w | Effects on workers | | |
| Route of exposur | e Acute | e Acu | te | Chronic | Chronic | Acute | Acute | Chronic | Chronic |
| | local | sys | temic | local | systemic | local | systemic | local | systemic |
| Oral | | | | | 0.83 | | | | 0.83 |
| | | | | | mg/kg/d | | | | mg/kg/d |
| Inhalation | | | | | 2.9 | | | | 4.9 |
| | | | | | mg/m3 | | | | mg/m3 |
| Skin | | | | | 0.83 | | | | 1.3 |
| | | | | | mg/kg/d | | | | mg/kg/d |

| | | | ISOBOR | NYL ACRYLATE | | | | | |
|--|---------------|-------------|---------|--------------|--------------------|----------|---------|----------|--|
| edicted no-effect cor | ncentration | - PNEC | | | | | | | |
| Normal value in fresh | water | | | | | 0,00092 | mg/l | | |
| Normal value in marii | ne water | | | | | 0,00009 | mg/l | | |
| | | | | | | 2 | | | |
| Normal value for fres | h water sedi | ment | | | | 0,145 | mg/kg | | |
| Normal value for mar | ine water se | diment | | | | 0,0145 | mg/kg | | |
| Normal value of STP | microorgani | sms | | | | 2 | mg/l | | |
| Normal value for the terrestrial compartment | | | | | | | mg/kg | | |
| ealth - Derived no-eff | ect level - D | NEL / DMEL | | | | | | | |
| | Effects or | n consumers | | | Effects on workers | | | | |
| Route of exposure | Acute | Acute | Chronic | Chronic | Acute | Acute | Chronic | Chronic | |
| | local | systemic | local | systemic | local | systemic | local | systemic | |
| Oral | | | | 0.83 | | | | | |
| | | | | mg/kg bw/d | | | | | |
| Skin | | | | 0.83 | | | | 1.39 | |
| | | | | mg/kg bw/d | | | | mg/kg | |
| | | | | J 0 | | | | bw/d | |

| | | | N,N-DIMETI | HYLACRYLAM | IDE | | | |
|-------------------------|----------------|-------------|------------|--------------------|-------|----------|---------|----------|
| redicted no-effect cor | ncentration | - PNEC | | | | | | |
| Normal value in fresh | water | | | | | 0,12 | mg/l | |
| Normal value in mari | ne water | | | | | 0,012 | mg/l | |
| Normal value for fres | h water sed | iment | | | | 0,509 | mg/kg | |
| Normal value for mar | ine water se | ediment | | | | 0,051 | mg/kg | |
| Normal value of STP | | | | | | 18 | mg/l | |
| Normal value for the | terrestrial co | mpartment | | | | 0,031 | mg/kg | |
| lealth - Derived no-eff | ect level - C | NEL / DMEL | | | | | | |
| | Effects o | n consumers | | Effects on workers | | | | |
| Route of exposure | Acute | Acute | Chronic | Chronic | Acute | Acute | Chronic | Chronic |
| | local | systemic | local | systemic | local | systemic | local | systemic |
| Oral | | | | 0,0147 | | | | |
| | | | | mg/kg/d | | | | |
| Inhalation | | | | 0,051 | | | | 0,207 |
| | | | | mg/m3 | | | | mg/m3 |
| Claim | | | | 0,179 | | | | 0,357 |
| Skin | | | | | | | | |



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 6 / 13

SECTION 8. Exposure controls/personal protection/

| | | TETF | RAHYDROFURI | FURYL METHA | CRYLATE | | | | | | |
|--|--|-------------|-------------|-------------|------------|----------|---------|----------|--|--|--|
| Predicted no-effect cor | ncentration | - PNEC | | | | | | | | | |
| Normal value in fresh | water | | | | | 0,347 | mg/l | | | | |
| Normal value in marir | Normal value in marine water 0,035 mg/l | | | | | | | | | | |
| Normal value for fresl | h water sedi | iment | | | | 2,12 | mg/kg/d | | | | |
| Normal value for mar | ine water se | ediment | | | | 0,212 | mg/kg/d | | | | |
| Normal value of STP | microorgani | isms | | | | 15,8 | mg/l | | | | |
| Normal value for the terrestrial compartment 0,221 mg/kg/d | | | | | | | | | | | |
| Health - Derived no-effe | Health - Derived no-effect level - DNEL / DMEL | | | | | | | | | | |
| | Effects or | n consumers | | | Effects on | workers | | | | | |
| Route of exposure | Acute | Acute | Chronic | Chronic | Acute | Acute | Chronic | Chronic | | | |
| | local | systemic | local | systemic | local | systemic | local | systemic | | | |
| Oral | | | | 0.5 | | • | | | | | |
| | | | | mg/kg/d | | | | | | | |
| Inhalation | | | | 0.87 | | | | 3.53 | | | |
| | | | | mg/m3 | | | | mg/m3 | | | |
| Skin | | | | 0.5 | | | | 1 | | | |
| | | | | mg/kg/d | | | | mg/kg/d | | | |

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

PropertiesValueInformationAppearanceliquidColourcolourlessOdourcharacteristicMelting point / freezing pointnot availableInitial boiling pointnot available



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 7 / 13

SECTION 9. Physical and chemical properties .../>

Flammability not available
Lower explosive limit not available
Upper explosive limit not available
Flash point > 100 °C
Auto-ignition temperature not available
Decomposition temperature not available

pH not available

Kinematic viscosity not available

Dynamic viscosity ~ 16000 mPa.s Thixo

Solubility not available

Partition coefficient: n-octanol/water not available
Vapour pressure not available
Density and/or relative density 1,1

Relative vapour density not available Particle characteristics not applicable Reason for missing data:substance/mixture is non-soluble (in water)

Temperature: 23 °C

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Strong reducing and oxidizing agents.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

E١



Permabond Engineering Adhesives

Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 8 / 13

SECTION 11. Toxicological information .../>>

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: >2000 mg/kg

2-HYDROXYETHYL METHACRYLATE

LD50 (Dermal): > 5000 mg/kg LD50 (Oral): > 5000 mg/kg

ISOBORNYL ACRYLATE

LD50 (Dermal): > 3000 mg/kg LD50 (Oral): 4350 mg/kg

N,N-DIMETHYLACRYLAMIDE

LD50 (Dermal): 720 mg/kg LD50 (Oral): 280 mg/kg

TETRAHYDROFURFURYL METHACRYLATE

LD50 (Oral): 3945 mg/kg

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 5000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

E١



Permabond Engineering Adhesives

Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 9 / 13

SECTION 11. Toxicological information .../>>

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

2-HYDROXYETHYL METHACRYLATE

 LC50 - for Fish
 > 100 mg/l/96h

 EC50 - for Crustacea
 380 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 836 mg/l/72h

ISOBORNYL ACRYLATE

LC50 - for Fish 0,704 mg/l/96h
EC50 - for Algae / Aquatic Plants 1,98 mg/l/72h
Chronic NOEC for Fish 0,431 mg/l
Chronic NOEC for Crustacea 0,092 mg/l
Chronic NOEC for Algae / Aquatic Plants 0,405 mg/l

N,N-DIMETHYLACRYLAMIDE

 LC50 - for Fish
 > 120 mg/l/96h

 EC50 - for Crustacea
 > 120 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 400 mg/l/72h

TETRAHYDROFURFURYL METHACRYLATE

 LC50 - for Fish
 34,7 mg/l/96h

 EC50 - for Crustacea
 69 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

 Chronic NOEC for Fish
 9,4 mg/l

 Chronic NOEC for Crustacea
 37,2 mg/l

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

 LC50 - for Fish
 6,53 mg/l/96h 48h

 EC50 - for Crustacea
 3,53 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 2,01 mg/l/72h

 EC10 for Algae / Aquatic Plants
 1,56 mg/l/72h

12.2. Persistence and degradability

2-HYDROXYETHYL METHACRYLATE

Rapidly degradable

ISOBORNYL ACRYLATE NOT rapidly degradable

N,N-DIMETHYLACRYLAMIDE NOT rapidly degradable

TETRAHYDROFURFURYL METHACRYLATE

NOT rapidly degradable

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

NOT rapidly degradable

12.3. Bioaccumulative potential

TETRAHYDROFURFURYL METHACRYLATE

Partition coefficient: n-octanol/water 1,38 Log Kow



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 10 / 13

SECTION 12. Ecological information .../>>

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0.1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE;

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE;

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE;

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE)



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 11 / 13

SECTION 14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID:

Class: 9

Label: 9

IMDG:

Class: 9

Label: 9

IATA:

Class: 9

Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA:

Ш

14.5. Environmental hazards

ADR / RID:

Environmentally Hazardous

IMDG:

Marine Pollutant

IATA:

Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:

HIN - Kemler: 90

Limited Quantities: 5 L

Tunnel restriction code: (-)

IMDG:

Special provision: -EMS: F-A, S-F Cargo:

Special provision:

Passengers:

Limited Quantities: 5 L Maximum quantity: 450 L

Maximum quantity: 450 L A97, A158, A197, A215 Packaging instructions: 964
Packaging instructions: 964

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

;

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

E١



Permabond Engineering Adhesives

Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 12 / 13

SECTION 15. Regulatory information .../>

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 1B
Repr. 2
Reproductive toxicity, category 1B
Repr. 2
Acute Tox. 3
Eye Dam. 1
Eye Irrit. 2
Skin Irrit. 2
Skin irritation, category 2
Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1Skin sensitization, category 1Skin Sens. 1BSkin sensitization, category 1B

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H360DMay damage the unborn child.H361fSuspected of damaging fertility.H301Toxic if swallowed.H311Toxic in contact with skin.H318Causes serious eye damage.H319Causes serious eye irritation.H315Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration



Permabond UV640

Revision nr.1 Dated 06/06/2023 First compilation Printed on 06/06/2023 Page n. 13 / 13

SECTION 16. Other information .../>>

- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.