



## SAFETY DATA SHEET

### Permabond ET5003B

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Permabond ET5003B

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Two-component, epoxy-based adhesive.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Permabond Engineering Adhesives Ltd.  
 Wessex Way  
 Colden Common  
 Winchester  
 Hampshire SO21 1WP  
 United Kingdom  
 Tel: +44 (0)1962 711 661  
 Fax: +44 (0)1962 711 662  
 info@permabond.co.uk

##### 1.4. Emergency telephone number

**Emergency telephone** CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

**National emergency telephone number** CHEMTREC Ireland: +(353)-19014670  
 CHEMTREC Australia: +(61)-290372994  
 CHEMTREC New Zealand: +(64)-98010034

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 3 - H412

##### 2.2. Label elements

###### Hazard pictograms



**Signal word** Danger

**Hazard statements** H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H317 May cause an allergic skin reaction.  
 H412 Harmful to aquatic life with long lasting effects.

## Permabond ET5003B

### Precautionary statements

P261 Avoid breathing vapour/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/ doctor.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

MERCAPTAN-TERMINATED OLIGOMER, ETHYLENE BIS(3-MERCAPTOPROPIONATE),  
 3-AMINOPROPYLDIMETHYLAMINE, 3-AMINOPROPYLTRIETHOXYSILANE

### 2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>MERCAPTAN-TERMINATED OLIGOMER</b>			<b>30-60%</b>
CAS number: 72244-98-5	EC number: 701-196-7	REACH registration number: 01-2120118957-46-XXXX	
<b>Classification</b> Skin Sens. 1B - H317 Aquatic Chronic 3 - H412			

<b>ETHYLENE BIS(3-MERCAPTOPROPIONATE)</b>			<b>5-10%</b>
CAS number: 22504-50-3			
<b>Classification</b> Acute Tox. 4 - H302 Skin Sens. 1A - H317 Aquatic Chronic 2 - H411			

<b>3-AMINOPROPYLDIMETHYLAMINE</b>			<b>1-5%</b>
CAS number: 109-55-7	EC number: 203-680-9	REACH registration number: 01-2119486842-27-XXXX	
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317			

## Permabond ET5003B

3-AMINOPROPYLTRIETHOXYSILANE			<1%
CAS number: 919-30-2	EC number: 213-048-4	REACH registration number: 01-2119480479-24-XXXX	
<b>Classification</b> Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317			

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. If symptoms develop, obtain medical attention
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Skin contact</b>	Skin irritation. Mild dermatitis, allergic skin rash.
<b>Eye contact</b>	May cause serious eye damage.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. Treat symptomatically.
-----------------------------	-----------------------------------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide, dry powder or water fog.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

<b>Hazardous combustion products</b>	Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NOx). Carbon monoxide, carbon dioxide, and unknown hydrocarbons.
--------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------

#### 5.3. Advice for firefighters

<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
------------------------------------------------------	-------------------------------------------------------------------------------------------------------

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	-------------------------------------------------------------------------------

#### 6.2. Environmental precautions

<b>Environmental precautions</b>	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	------------------------------------------------------------------

## PermaBond ET5003B

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal. Wash area with soap and water.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in closed original container at temperatures between 5°C and 25°C.

### 7.3. Specific end use(s)

**Specific end use(s)** Adhesive. Sealant.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### MERCAPTAN-TERMINATED OLIGOMER (CAS: 72244-98-5)

<b>DMEL</b>	Workers - Inhalation; Long term systemic effects: 22 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 2.7 mg/kg/day
<b>PNEC</b>	Fresh water; 70 µg/l marine water; 7 µg/l STP; 10 mg/l Sediment (Freshwater); 322 µg/kg, dw Sediment (Marinewater); 32 µg/kg, dw Soil; 23 µg/kg, dw

#### 3-AMINOPROPYLDIMETHYLAMINE (CAS: 109-55-7)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 1.2 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 1.2 mg/m <sup>3</sup>
<b>PNEC</b>	Fresh water; 0.073 mg/l marine water; 0.007 mg/l STP; 69.5 mg/l Sediment (Freshwater); 0.735 mg/kg Sediment (Marinewater); 0.073 mg/kg

#### 3-AMINOPROPYLTRIETHOXSILANE (CAS: 919-30-2)

<b>DNEL</b>	Workers - Inhalation; Short term systemic effects: 59 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects: 59 mg/m <sup>3</sup> Workers - Dermal; Short term systemic effects: 8.3 mg/kg/day Workers - Dermal; Short term systemic effects: 8.3 mg/m <sup>3</sup>
-------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Permabond ET5003B

### PNEC

Fresh water; 0.33 mg/l  
marine water; 0.033 mg/l  
Sediment (Freshwater); 0.26 mg/kg  
Sediment (Marinewater); 0.026 mg/kg  
Soil; 0.04 mg/kg  
STP; 13 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation.

#### Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

#### Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness:  $\geq 0.4$  mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness:  $\geq 0.4$  mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

#### Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

#### Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

#### Respiratory protection

Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Black.
Odour	Mild.
Odour threshold	Not available.
pH	Not available.
Melting point	Not determined.
Initial boiling point and range	Not applicable.

## Permabond ET5003B

Flash point	>100°C
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not determined.
Vapour density	Not available.
Relative density	1.5
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not available.
Viscosity	30000 mPa s @ 25°C
Explosive properties	Not determined.
Oxidising properties	Not determined.

### 9.2. Other information

Other information	Not relevant.
-------------------	---------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	Under normal conditions of storage and use, no hazardous reactions will occur.
------------	--------------------------------------------------------------------------------

### 10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	----------------------------------------

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Reactions with the following materials may generate heat: Amines.
------------------------------------	-------------------------------------------------------------------

### 10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	-----------------------------------------------------

### 10.5. Incompatible materials

Materials to avoid	Strong oxidising agents. Strong acids. Strong alkalis.
--------------------	--------------------------------------------------------

### 10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.
----------------------------------	----------------------------------------------------------------------------------------------------------

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological effects	The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.
-----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Skin sensitisation

## PermaBond ET5003B

<b>Skin sensitisation</b>	May cause sensitisation by skin contact.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	None under normal conditions.
<b>Inhalation</b>	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. In high concentrations, vapours may irritate throat and respiratory system and cause coughing.
<b>Ingestion</b>	No harmful effects expected from quantities likely to be ingested by accident.
<b>Skin contact</b>	Irritating to skin. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye damage.

### SECTION 12: Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Avoid release to the environment.

#### 12.1. Toxicity

**Toxicity** The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is not readily biodegradable.

#### 12.3. Bioaccumulative potential

**Partition coefficient** Not available.

#### 12.4. Mobility in soil

**Mobility** No data available. The product has poor water-solubility.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
<b>Disposal methods</b>	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
<b>Waste class</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

### SECTION 14: Transport information

**General** The product is not classified as dangerous for carriage.

## Permabond ET5003B

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

Not applicable.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
<b>Guidance</b>	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>Revision date</b>	10/11/2021
<b>Revision</b>	1



## Permabond ET5003B

### Hazard statements in full

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.