

Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 1 / 12

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permahond ET5453B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive

Identified Uses Industrial Professional Consumer
Use -

1.3. Details of the supplier of the safety data sheet

Name
Full address
District and Country

Name
Permabond Engineering Adhesives
Niederkasseler Lohweg 18
40547
Düsseldorf
Germany
Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2	H361f	Suspected of damaging fertility.
Acute toxicity, category 4	H302	Harmful if swallowed.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic	H410	Very toxic to aquatic life with long lasting effects.
toxicity, category 1		



Permabond ET5453B

Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 2 / 12

SECTION 2. Hazards identification

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









Signal words: Danger

Hazard statements:

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.

Contains: 4-TERT-BUTYLPHENOL

2.2.4- TRIMETHYLHEXAMETHYLENEDIAMINE

M-PHENYLENEBIS (METHYLAMINE)

PARAFORMALDEHYDE, POLIMERIC REACTION PRODUCTS WITH 4- TERT-BUTYLPHENOL,

MPHENYLENBIS (METHYLAMINE) AND TRIMETHYLHEXANE- 1,6- DIAMINE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product contains substances with endocrine disrupting properties in concentration ≥ 0,1%:

4-TERT-BUTYL PHENOL

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Classification (EC) 1272/2008 (CLP) x = Conc. %

4-TERT-BUTYLPHENOL

INDFX 604-090-00-8 $30 \le x < 60$ Repr. 2 H361f, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 1 H410

202-679-0 FC CAS 98-54-4

REACH Reg. 01-

01-2119489419-21-XXXX



Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 3 / 12

SECTION 3. Composition/information on ingredients

M-PHENYLENEBIS (METHYLAMINE)

INDEX 10 ≤ x < 25 Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1

H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071

EC 216-032-5 STA Oral: 500 mg/kg, STA Inhalation vapours: 11 mg/l CAS 1477-55-0

REACH Reg. 01-2119480150-50-XXXX 2,2,4- TRIMETHYLHEXAMETHYLENEDIAMINE

INDEX 10 ≤ x < 25 Acute Tox. 4 H302, Skin Corr. 1A H314, Eye Dam. 1 H318, Skin Sens. 1A

H317

EC 247-063-2 STA Oral: 500 mg/kg

CAS 25513-64-8

REACH Reg. 01-2119560598-25-XXXX

PARAFORMALDEHYDE, POLIMERIC REACTION PRODUCTS WITH 4- TERT-BUTYLPHENOL, MPHENYLENBIS (METHYLAMINE)

AND TRIMETHYLHEXANE- 1,6- DIAMINE

INDEX 10 ≤ x < 25 Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC CAS

PHENOL, STYRENATED

INDEX $5 \le x < 10$ Aquatic Chronic 2 H411

EC 262-975-0 CAS 61788-44-1

REACH Reg. 01-2119980970-27-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request

medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Give plenty of water to drink. Do not cause vomiting. Consult a doctor.

Inhalation: Move the exposed person to fresh air. Consult a doctor in case of serious symptoms or persistent.

persisterit.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with



Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 4 / 12

self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 8A

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DNK Danmark Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
NOR Norge Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og

arbeidstilligbet samt striktensikogrupper for blologiske laktorer (forskrift om tiltaks- og

grenseverdier), 21. august 2018 nr. 1255

SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu

(Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)

TLV-ACGIH ACGIH 2022



Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 5 / 12

SECTION 8. Exposure controls/personal protection .../

M-PHENYLENEBIS (METHYLAMINE)								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15	min	Remarks / C	bservations	
		mg/m3	ppm	mg/m3	ppm			
TLV	DNK			0,1 (C)	0,02 (C)	SKIN		
VLEP	FRA			0,1				
TLV	NOR	0,1						
MV	SVN	0,1						
TLV-ACGIH				0,018 (C)		SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water					0,094	mg/l		
Normal value in marine water					0,0094	mg/l		
Normal value for fresh water sediment					0,43	mg/kg		
Normal value for marine water sediment						0,043	mg/kg	
Normal value of STP microorganisms					10	mg/l		

PHENOL, STYRENATED		
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,03	mg/l
Normal value in marine water	0,003	mg/l

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Information



Permabond ET5453B

Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 6 / 12

Reason for missing data:substance/mixture is

water)

non-soluble

Temperature: 23 °C

SECTION 9. Physical and chemical properties

Appearance liquid Colour Amber Odour characteristic Melting point / freezing point not available Initial boiling point not available Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point 100 °C not available Auto-ignition temperature Decomposition temperature not available

not available

not available Kinematic viscosity Dynamic viscosity 550 mPas Solubility not available Partition coefficient: n-octanol/water not available not available Vapour pressure

Density and/or relative density

not available Relative vapour density Particle characteristics not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Strong oxidizing agents, Reducing agents, strong acids and bases.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See the reactivity section.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

F١



Permabond Engineering Adhesives

Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 7 / 12

SECTION 11. Toxicological information .../>>

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: 1562,50 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

Corrosive to the respiratory tract.

4-TERT-BUTYLPHENOL

 LD50 (Dermal):
 > 2000 mg/kg

 LD50 (Oral):
 > 2000 mg/kg

 LC50 (Inhalation vapours):
 > 5,6 mg/l/4h

M-PHENYLENEBIS (METHYLAMINE)

LD50 (Dermal): 3100 mg/kg Rat

LD50 (Oral): > 200 mg/kg Rat - Sprague-Dawley

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LC50 (Inhalation vapours): 1,34 mg/l/4h Rat - Wistar

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

2,2,4- TRIMETHYLHEXAMETHYLENEDIAMINE

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

PHENOL, STYRENATED

LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 2000 mg/kg

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY





Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 8 / 12

SECTION 11. Toxicological information .../>>

Suspected of damaging fertility

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

4-TERT-BUTYLPHENOL

LC50 - for Fish 5,1 mg/l/96h (Pimephales promelas) EC50 - for Crustacea 3,9 mg/l/48h Daphnia magna)

EC50 - for Algae / Aquatic Plants 14 mg/l/72h (Pseudokirchnerilla subcapitata)

M-PHENYLENEBIS (METHYLAMINE)

LC50 - for Fish 87,6 mg/l/96h Oryzias latipes EC50 - for Crustacea 15,2 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 20,3 mg/l/72h Pseudokirchnerella subcapitata

PHENOL, STYRENATED

 LC50 - for Fish
 14,8 mg/l/96h

 EC50 - for Crustacea
 4,6 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 3,14 mg/l/72h

12.2. Persistence and degradability

M-PHENYLENEBIS (METHYLAMINE)

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

M-PHENYLENEBIS (METHYLAMINE)

Partition coefficient: n-octanol/water 0,18

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny:

4-TERT-BUTYLPHENOL



Permabond ET5453B

Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 9 / 12

SECTION 12. Ecological information

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2735

14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-

Benzoldimethanamine, 4-tert-butylphenol)

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-IMDG:

Benzoldimethanamine, 4-tert-butylphenol)

IATA: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-

Benzoldimethanamine, 4-tert-butylphenol)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

Class: 8 Label: 8 IMDG:

IATA: Class: 8 Label: 8



14.4. Packing group

IMDG:

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO NO IATA:

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Quantities: 1 L Tunnel restriction code: (E)

Special provision: 274

EMS: F-A, S-B Limited Quantities: 1 L IATA: Cargo: Maximum quantity: 30 L Packaging instructions: 855

Passengers: Maximum quantity: 1 L Packaging instructions: 851

A3, A803 Special provision:

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 10 / 12

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: E

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

4-TERT-BUTYLPHENOL

REACH Reg.: 01-

01-2119489419-21-XXXX

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2 Reproductive toxicity, category 2 Acute Tox. 4 Acute toxicity, category 4 Skin Corr. 1A Skin corrosion, category 1A Skin Corr. 1B Skin corrosion, category 1B Eye Dam. 1 Serious eye damage, category 1 Skin irritation, category 2 Skin Irrit. 2 Skin Sens. 1 Skin sensitization, category 1 Skin sensitization, category 1A Skin Sens. 1A Skin Sens. 1B Skin sensitization, category 1B

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

E١



Permabond Engineering Adhesives

Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 11 / 12

SECTION 16. Other information .../>>

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP) 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy





Permabond ET5453B

Revision nr.1 Dated 04/01/2024 First compilation Printed on 04/01/2024 Page n. 12 / 12

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.