Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Permabond TA4550A**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses	Industrial	Professional	Consumer
Use	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives**
Full address **Niederkasseler Lohweg 18**
District and Country **40547 Düsseldorf**
Germany
Tel. +44 (0)1962 711 661

e-mail address of the competent person responsible for the Safety Data Sheet **info.europe@permabond.com**

Supplier:
Permabond Engineering Adhesives Ltd
Wessex Way, Colden Common,
Winchester, Hampshire SO21 1WP, UK
tel: +44 (0)1962 711 661
mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to **+44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)**

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal word: Danger

Hazard statements:

H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P273	Avoid release to the environment.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.

Contains:
Acrylic acid
Benzyl methacrylate
Maleic acid
2-hydroxyethyl methacrylate
4-Methoxyphenol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
Benzyl methacrylate			
INDEX		10 ≤ x < 30	**Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317**
EC	*219-674-4*		**STOT SE 3 H335: ≥ 10%**
CAS	*2495-37-6*		
REACH Reg.	*01-2119960155-39-XXXX*		
Isobornyl methacrylate			
INDEX		10 ≤ x < 20	**Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412**
EC	*231-403-1*		
CAS	*7534-94-3*		
REACH Reg.	*01-2119886505-27-XXXX*		
2-hydroxyethyl methacrylate			
INDEX	*607-124-00-X*	5 ≤ x < 10	**Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317**
EC	*212-782-2*		
CAS	*868-77-9*		
REACH Reg.	*01-2119490169-29-XXXX*		

SECTION 3. Composition/information on ingredients ... / >>

Acrylic acid			
INDEX	*607-061-00-8*	5 ≤ x < 10	**Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: D**
EC	*201-177-9*		**STOT SE 3 H335: ≥ 1%**
CAS	*79-10-7*		**LD50 Oral: 1500 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l**
REACH Reg.	*01-2119452449-31-XXXX*		
Maleic acid			
INDEX	*607-095-00-3*	1 ≤ x < 5	**Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317**
EC	*203-742-5*		**ATE Oral: 500 mg/kg**
CAS	*110-16-7*		
REACH Reg.	*01-2119488705-25-XXXX*		
POLY[OXY(METHYL-1,2-ETHANEDIYL)], .ALPHA.-(2-METHYL-1-OXO-2- PROPENYL)-.OMEGA.- (PHOSPHONOOXY)-			
INDEX		1 ≤ x < 3	**Eye Dam. 1 H318, Skin Irrit. 2 H315**
EC	*680-385-5*		
CAS	*95175-93-2*		
Dodecyl methacrylate			
INDEX	*607-247-00-9*	1 ≤ x < 5	**STOT SE 3 H335**
EC	*205-570-6*		**STOT SE 3 H335: ≥ 10%**
CAS	*142-90-5*		
REACH Reg.	*01-2119489778-11-XXXX*		
Cumene hydroperoxide			
INDEX	*617-002-00-8*	0,1 ≤ x < 1	**Org. Perox E H242, Acute Tox. 3 H331, Acute Tox. 4 H302, Acute Tox. 4 H312, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 2 H411**
EC	*201-254-7*		**Skin Corr. 1B H314: ≥ 10%, Skin Irrit. 2 H315: ≥ 3% - < 10%, Eye Dam. 1 H318: ≥ 3% - < 10%, Eye Irrit. 2 H319: ≥ 1% - < 3%, STOT SE 3 H335: ≥ 1%**
CAS	*80-15-9*		**LD50 Oral: 382 mg/kg, LD50 Dermal: 1400 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l**
REACH Reg.	*01-2119475796-19-XXXX*		
Triethylenglycol-bis[3-(3-t-butyl-4-hydroxy -5-methylpheyl)propionate]			
INDEX		0,25 ≤ x < 1	**Aquatic Chronic 1 H410 M=1**
EC	*253-039-2*		
CAS	*36443-68-2*		
REACH Reg.	*01-2119956160-44-XXXX*		
4-Methoxyphenol			
INDEX	*604-044-00-7*	0,1 ≤ x < 1	**Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Chronic 3 H412**
EC	*205-769-8*		**ATE Oral: 500 mg/kg**
CAS	*150-76-5*		
REACH Reg.	*01-2119541813-40-XXXX*		
2,6-di-tert-butyl-p-cresol			
INDEX		0,1 ≤ x < 0,25	**Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1**
EC	*204-881-4*		
CAS	*128-37-0*		
REACH Reg.	*01-2119480433-40-XXXX*		
PHOSPHORIC ACID			
INDEX	*015-011-00-6*	0 < x < 0,1	**Met. Corr. 1 H290, Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B**
EC	*231-633-2*		**Skin Corr. 1B H314: ≥ 25%, Skin Irrit. 2 H315: ≥ 10% - < 25%, Eye Dam. 1 H318: ≥ 25%, Eye Irrit. 2 H319: ≥ 10% - < 25%**
CAS	*7664-38-2*		**LD50 Oral: 1530 mg/kg**

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Cumene hydroperoxide
Specific Conc. Limits H335: C<10%

SECTION 4. First aid measures

4.1. Description of first aid measures

SKIN: Wash skin thoroughly with soap and water. If symptoms occur, seek medical attention. EYES: Be sure to remove any contact lenses before rinsing eyes. Promptly rinse eyes thoroughly with water while holding eyelids open. Continue rinsing for at least 15 minutes. Seek medical attention if discomfort persists. INGESTION: Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce

SECTION 4. First aid measures ... / >>

vomiting. Seek medical attention. INHALING: Move exposed person to fresh air. Seek medical attention if symptoms are severe or persistent.

Rescuer protection

Information not available

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash.
Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

Means to have available in the workplace for specific and immediate treatment

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE
Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO_2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 8A

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

ALB	Shqipëria	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES “PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË”
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
DNK	Danmark	BEK nr 291 af 19/03/2024 (Historisk) Bekendtgørelse om grænseværdier for stoffer og materialer (kemiske agenser) i arbejdsmiljøet
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ’’σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία’’»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	PRAVILNIK O IZMJENAMA I DOPUNAMA PRAVILNIKA O ZAŠTITI RADNIKA OD IZLOŽENOSTI OPASNIM KEMIKALIJAMA NA RADU, GRANIČNIM VRIJEDNOSTIMA IZLOŽENOSTI I BIOLOŠKIM GRANIČNIM VRIJEDNOSTIMA
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" Oficiālās publikācijas Nr.: 2024/65.2
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. 10. april 2024 kl. 13.55
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr. 2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a agentes cancerígenos ou mutagénicos e procede à quarta alteração
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24

SECTION 8. Exposure controls/personal protection ... / >>

		czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea şi completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerinţelor minime de securitate şi sănătate pentru protecţia lucrătorilor împotriva riscurilor legate de expunerea la agenţi ca
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SWE	Sverige	Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för luftvägsexponering i arbetsmiljön
SVK	Slovensko	121_2024 Z. z. Nariadenie vlády o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym, mutagénnym alebo reprodukčne toxickým faktorom pri práci
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	ACGIH	ACGIH 2025

2,6-di-tert-butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	10		40		
TLV	DNK	10		20		
VLA	ESP	10				
VLEP	FRA	10				
HTP	FIN	10		20		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value for fresh water sediment	0,458	mg/kg/d
Normal value for marine water sediment	0,046	mg/kg/d
Normal value for marine water, intermittent release	0,002	mg/l
Normal value of STP microorganisms	0,017	mg/l
Normal value for the food chain (secondary poisoning)	16,67	mg/kg
Normal value for the terrestrial compartment	0,054	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1 mg/kg bw/d		0,25 mg/kg bw/d				
Inhalation		3,1 mg/m3		0,78 mg/m3		18 mg/m3		4,4 mg/m3
Skin		6,7 mg/kg bw/d		1,7 mg/kg bw/d		19 mg/kg bw/d		4,7 mg/kg bw/d

Maleic acid

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	334	mg/kg
Normal value for marine water sediment	334	mg/kg
Normal value for marine water, intermittent release	4281	mg/l
Normal value of STP microorganisms	44,6	mg/l
Normal value for the terrestrial compartment	42	mg/kg

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					3 mg/m3	3 mg/m3	3 mg/m3	3 mg/m3

SECTION 8. Exposure controls/personal protection ... / >>

2-hydroxyethyl methacrylate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	NOR	11	2	11	2	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,0482	mg/l
Normal value for fresh water sediment	3,79	mg/kg
Normal value for marine water sediment	3,79	mg/kg
Normal value for fresh water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0.83 mg/kg/d				0.83 mg/kg/d
Inhalation				2.9 mg/m3				4.9 mg/m3
Skin				0.83 mg/kg/d				1.3 mg/kg/d

Isobornyl methacrylate

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00446	mg/l
Normal value for fresh water sediment	0,604	mg/kg
Normal value of STP microorganisms	2,45	mg/l
Normal value for the terrestrial compartment	0,118	mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

Acrylic acid

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	29	10	59	20		STEL: 1'
TLV	CZE	29	9,686	59	19,706		NPK-P= 1 min
AGW	DEU	30	10	30 (C)	10 (C)		
MAK	DEU	30	10	30	10		
TLV	DNK			5,9	2	SKIN	E
TLV	EST	29	10	45	15		
VLEP	FRA	29	10	59	20		
HTP	FIN	6	2	45 (C)	15 (C)		
TLV	GRC	29	10	59	20		STEL: 1'
AK	HUN	29		59			CK: 1 min
GVI/KGVI	HRV	29	10	59	20		KGVI: 1 min
VLEP	ITA	29	10	59	20	SKIN	STEL: 1 min
RD	LTU	29	10	59 (C)	20 (C)		
RV	LVA	5	1,7	59	20		STEL: 1min
TLV	NOR	29	10	59	20		
TGG	NLD	29		59			TGG: 1 min
VLE	PRT	29	10	59	20		STEL: 1 min
NDS/NDSCh	POL	10		29,5		SKIN	
TLV	ROU	29	10	59	20		STEL: 1'
ПДК	RUS	5		15			п
NPEL	SVK	29	10	59	20		NPEL: 1'
WEL	GBR	29	10	59	20		STEL: 1-minute
OEL	EU	29	10	59	20		STEL: 1'
ACGIH		6	2			SKIN	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,003	mg/l
Normal value in marine water	0,0003	mg/l
Normal value for fresh water sediment	0,0236	mg/kg
Normal value for marine water sediment	0,00236	mg/kg
Normal value of STP microorganisms	0,9	mg/l
Normal value for the terrestrial compartment	1	mg/kg

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					30 mg/m3		30 mg/m3	
Skin					1 mg/cm2		1 mg/cm2	

Benzyl methacrylate

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,01	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,423	mg/kg/d
Normal value for marine water sediment	0,042	mg/kg/d
Normal value of STP microorganisms	1,33	mg/l
Normal value for the terrestrial compartment	0,079	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		LOW		4,17 mg/kg bw/d				
Inhalation				7,2 mg/m3				24,2 mg/m3
Skin	MED	LOW		4,17 mg/kg bw/d	MED	LOW		6,94 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Dodecyl methacrylate

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Skin				25 mg/kg bw/d				41.66 mg/kg bw/d

PHOSPHORIC ACID

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ALB	1		2		
TLV	BGR	1		2		
TLV	CZE	1	0,25	2	0,49	
AGW	DEU	2		4		INHAL
MAK	DEU	2		4		INHAL
TLV	DNK	1		2		E
VLA	ESP	1		2		
TLV	EST	1		2		
VLEP	FRA	1	0,2	2	0,5	
HTP	FIN	1		2		
TLV	GRC	1		3		
AK	HUN	1		2		
GVI/KGVI	HRV	1		2		
VLEP	ITA	1		2		
RD	LTU	1		2		
RV	LVA	1		2		
TLV	NOR	1				
TGG	NLD	1		2		
VLE	PRT	1		2		
NDS/NDSCh	POL	1		2		
TLV	ROU	1		2		
NGV/KGV	SWE	1		2		
NPEL	SVK	1		2		
MV	SVN	1		2		INHAL
ESD	TUR	1		2		
WEL	GBR	1		2		
OEL	EU	1		2		
ACGIH		1		3		

Cumene hydroperoxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
RV	LVA	1				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0031	mg/l
Normal value in marine water	0,00031	mg/l
Normal value for fresh water sediment	0,023	mg/kg
Normal value for marine water sediment	0,0023	mg/kg
Normal value for water, intermittent release	0,031	mg/l
Normal value of STP microorganisms	0,35	mg/l
Normal value for the terrestrial compartment	0,0029	mg/kg

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								6 mg/m3

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

SECTION 8. Exposure controls/personal protection ... / >>

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.
HAND PROTECTION
Protect hands with category III work gloves.
The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.
SKIN PROTECTION
Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.
EYE PROTECTION
Wear a hood visor or protective visor combined with airtight goggles (see standard EN ISO 16321).
RESPIRATORY PROTECTION
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.
ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.
Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties		Value		Information
Appearance		liquid		
Colour		yellow		
Odour		characteristic		
Melting point / freezing point		not available		
Initial boiling point		not available		
Flammability		not available		
Lower explosive limit		not available		
Upper explosive limit		not available		
Flash point	>	100	°C	
Auto-ignition temperature		not available		
Decomposition temperature		not available		
pH		not available		Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity		not available		
Dynamic viscosity		~ 150000 mPa.s	Thixo	Temperature: 25 °C
Solubility		not available		
Partition coefficient: n-octanol/water		not available		
Vapour pressure		not available		
Density and/or relative density		1		
Relative vapour density		not available		
Particle characteristics		not applicable		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

SECTION 9. Physical and chemical properties ... / >>

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Acrylic acid
Keep away from: oxidising agents.Maintaining a temperature of less than 13°C/55°F.May polymerise if exposed to: heat.
PHOSPHORIC ACID
Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Acrylic acid
Risk of explosion on contact with: oxidising agents,oxygen,peroxides.May polymerise on contact with: alkaline hydroxides,amines,ammonia,sulphuric acid.Forms explosive mixtures with: hot air.
PHOSPHORIC ACID
Risk of explosion on contact with: nitromethane.May react dangerously with: alkalis,sodium borohydride.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Acrylic acid
Avoid exposure to: light,sources of heat,naked flames.Avoid contact with: oxygen.

10.5. Incompatible materials

Acrylic acid
Incompatible with: peroxides,oxidising substances,strong acids,strong bases,amines,iron salts,oleum,chlorosulphuric acid.
PHOSPHORIC ACID
Incompatible with: metals,strong alkalis,aldehydes,organic sulphides,peroxides.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

PHOSPHORIC ACID
May develop: phosphoryl oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

SECTION 11. Toxicological information ... / >>

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Benzyl methacrylate

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	3980 mg/kg

Isobornyl methacrylate

LD50 (Dermal):	> 3000 mg/kg
LD50 (Oral):	> 2000 mg/kg

2-hydroxyethyl methacrylate

LD50 (Dermal):	> 5000 mg/kg
LD50 (Oral):	> 5000 mg/kg

Acrylic acid

LD50 (Dermal):	> 2000 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	1500 mg/kg Rat
LC50 (Inhalation vapours):	> 5,1 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Maleic acid

LD50 (Dermal):	> 400 mg/kg
LD50 (Oral):	2870 mg/kg
ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation mists/powders):	> 0,72 mg/l/1h

Dodecyl methacrylate

LD50 (Dermal):	> 3000 mg/kg
LD50 (Oral):	> 5000 mg/kg

Cumene hydroperoxide

LD50 (Dermal):	1400 mg/kg
LD50 (Oral):	382 mg/kg
LC50 (Inhalation mists/powders):	1,37 mg/l/4h
ATE (Inhalation mists/powders):	0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Triethylenglycol-bis[3-(3-t-butyl-4-hydroxy -5-methylpheyl)propionate]

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 7000 mg/kg

4-Methoxyphenol

ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

2,6-di-tert-butyl-p-cresol

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 2930 mg/kg

PHOSPHORIC ACID

LD50 (Dermal):	2740 mg/kg Rabbit
LD50 (Oral):	1530 mg/kg Rat
LC50 (Inhalation mists/powders):	> 0,85 mg/l/1h Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

SECTION 11. Toxicological information ... / >>

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Benzyl methacrylate	
LC50 - for Fish	4,67 mg/l/96h
EC50 - for Algae / Aquatic Plants	2,8 mg/l/72h
EC10 for Crustacea	1,03 mg/l/21d Daphnia magna
EC10 for Algae / Aquatic Plants	1,08 mg/l/72h
Isobornyl methacrylate	
LC50 - for Fish	1,79 mg/l/96h
EC50 - for Crustacea	> 2,57 mg/l/48h
EC50 - for Algae / Aquatic Plants	2,66 mg/l/72h
EC10 for Algae / Aquatic Plants	0,751 mg/l/72h
Chronic NOEC for Crustacea	0,233 mg/l
2-hydroxyethyl methacrylate	
LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	380 mg/l/48h
EC50 - for Algae / Aquatic Plants	836 mg/l/72h
Acrylic acid	
LC50 - for Fish	315 mg/l/96h Leuciscus idus melanotus
EC50 - for Crustacea	765 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	118 mg/l/72h Chlorococcales
Maleic acid	
LC50 - for Fish	75 mg/l/96h
EC50 - for Crustacea	42,81 mg/l/48h
EC50 - for Algae / Aquatic Plants	74,32 mg/l/72h

SECTION 12. Ecological information ... / >>

Dodecyl methacrylate
LC50 - for Fish > 10000 mg/l/96h

Cumene hydroperoxide
LC50 - for Fish 3,9 mg/l/96h
EC50 - for Crustacea 18,84 mg/l/48h
EC50 - for Algae / Aquatic Plants 3,1 mg/l/72h
Chronic NOEC for Crustacea 9,15 mg/l
Chronic NOEC for Algae / Aquatic Plants 1 mg/l

Triethylenglycol-bis[3-(3-t-butyl-4-hydroxy -5-methylpheyl)propionate]
LC50 - for Fish > 43 mg/l/96h
EC50 - for Crustacea > 100 mg/l/48h

2,6-di-tert-butyl-p-cresol
LC50 - for Fish > 0,57 mg/l/96h
EC50 - for Crustacea 0,48 mg/l/48h
EC50 - for Algae / Aquatic Plants 0,4 mg/l/72h
Chronic NOEC for Crustacea 0,316 mg/l

12.2. Persistence and degradability

Isobornyl methacrylate
Rapidly degradable

2-hydroxyethyl methacrylate
Rapidly degradable

Acrylic acid
Solubility in water 1000000 mg/l
Rapidly degradable

Cumene hydroperoxide
NOT rapidly degradable

2,6-di-tert-butyl-p-cresol
NOT rapidly degradable

PHOSPHORIC ACID
Solubility in water > 850000 mg/l
Degradability: information not available

12.3. Bioaccumulative potential

Acrylic acid
Partition coefficient: n-octanol/water 0,46
BCF 0,491

12.4. Mobility in soil

Acrylic acid
Partition coefficient: soil/water 0,78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 3265

14.2. UN proper shipping name

ADR / RID:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Acrylic acid; Maleic acid)
IMDG:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Acrylic acid; Maleic acid)
IATA:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Acrylic acid; Maleic acid)

14.3. Transport hazard class(es)

ADR / RID:	Class: 8	Label: 8
IMDG:	Class: 8	Label: 8
IATA:	Class: 8	Label: 8







14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	not marine pollutant
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80 Special provision: 274	Limited Quantities: 1 lt	Tunnel restriction code: (E)
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 30 L Maximum quantity: 1 L A3, A803	Packaging instructions: 855 Packaging instructions: 851

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006
Product
Point 3 - 40
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)
WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Org. Perox E	Organic peroxide, type E
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H290	May be corrosive to metals.

SECTION 16. Other information ... / >>

H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY
1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148

SECTION 16. Other information ... / >>

18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:
The following sections were modified:
03.