

# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 1 / 11

# **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name Permabond ES578

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive

Identified Uses Industrial Professional Consumer
Use -

#### 1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives
Full address Niederkasseler Lohweg 18
District and Country 40547 Düsseldorf
Germany

Tel. +44 (0)1962 711 661

info.europe@permabond.com

e-mail address of the competent person

responsible for the Safety Data Sheet

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

#### 1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 ( 8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

## **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

Skin irritation, category 2

Skin sensitization, category 1

Hazardous to the aquatic environment, chronic toxicity, category 2

Has Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 2 / 11

### SECTION 2. Hazards identification .../>

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

**P273** Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Contains: EPOXY RESIN (Number average MW <= 700 )

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq 0.1\%$ .

## **SECTION 3. Composition/information on ingredients**

### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

EPOXY RESIN (Number average MW <= 700)

INDEX 30 ≤ x < 60 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2

H411, EUH205

EC 216-823-5 Skin Irrit. 2 H315: ≥ 5%, Eye Irrit. 2 H319: ≥ 5%

CAS 1675-54-3

REACH Reg. 01-2119456619-26-XXXX METHYLENE DIPHENYL BIS(DIMETHYL UREA)

INDEX  $1 \le x < 5$  Aquatic Chronic 3 H412

EC 423-370-9 CAS 10097-09-3 REACH Reg. 01-0000016986-54

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 3 / 11

### SECTION 4. First aid measures .../>>

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash

Readyly and abundantly the eyes with water keeping the eyelids open.

Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink.

Do not cause vomiting. Consult a doctor.

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or

persistent.

### 4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash.

Contact with eyes: irritating and can cause redness and pain.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 4 / 11

# **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s)

Adhesive

# **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory references:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung				
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56				
ESP	España	Límites de exposición profesional para agentes químicos en España 2021				
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para				

Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os

riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

		EPO)	(Y RESIN (Num	ber average N	/IW <= 700 )			
redicted no-effect cor	ncentration		,		,			
Normal value in fresh	water					0,006	mg/l	
Normal value in marine water							mg/l	
Normal value for fresh water sediment							mg/kg	
Normal value for marine water sediment							mg/kg	
Normal value of STP microorganisms 10								
Normal value of STP microorganisms 10 mg/l Normal value for the food chain (secondary poisoning) 11 mg/kg								
Normal value for the terrestrial compartment 0,065 mg/kg								
ealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on consumers Effects on wo							
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0,5				
				mg/kg/d				
Inhalation				0,87				4,93
				mg/m3				mg/m3
Skin				0,0893				0,75
				mg/kg/d				mg/kg/d

METHYLENE DIPHENYL BIS(DIMETHYL UREA)								
Threshold Limit Value								
Type	Country	Country TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU	4				INHAL		
MAK	DEU	1,5				THORA		
VLA	ESP	3				RESP		
VLA	ESP	10				THORA		
VLE	PRT	3				INHAL		
VLE	PRT	10				THORA		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 5 / 11

### SECTION 8. Exposure controls/personal protection .../

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

# **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Properties		Value	Information		
Appearance		paste			
Colour		black			
Odour		mild			
Melting point / freezing point		not available			
Initial boiling point		not available			
Flammability		not available			
Lower explosive limit		not available			
Upper explosive limit		not available			
Flash point	>	100 °C			
Auto-ignition temperature		not available			
Decomposition temperature		not available			
рН		not available	Reason for missing	data:subs	tance/mixture is
			non-soluble	(in	water)
Kinematic viscosity		not available			
Dynamic viscosity		~ 700000 mPa.s Thixo	Temperature: 23 °C	;	
Solubility		not available			
Partition coefficient: n-octanol/water		not available			
Vapour pressure		not available			
Density and/or relative density		1,6			
Relative vapour density		not available			
Particle characteristics		not applicable			

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available





# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 6 / 11

## SECTION 9. Physical and chemical properties .../>

9.2.2. Other safety characteristics

Information not available

## **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Strong reducing and oxidizing agents.

#### 10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

### ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

EPOXY RESIN (Number average MW <= 700)

LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 2000 mg/kg

METHYLENE DIPHENYL BIS(DIMETHYL UREA)

LD50 (Dermal): > 2000 mg/kg LD50 (Oral): 5000 mg/kg



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 7 / 11

## SECTION 11. Toxicological information .../>>

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

#### 12.1. Toxicity

EPOXY RESIN (Number average MW <= 700)

 LC50 - for Fish
 2 mg/l/96h

 EC50 - for Crustacea
 1,8 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 11 mg/l/72h

 Chronic NOEC for Crustacea
 0,3 mg/l

 Chronic NOEC for Algae / Aquatic Plants
 4,2 mg/l

METHYLENE DIPHENYL BIS(DIMETHYL UREA)

 LC50 - for Fish
 > 302 mg/l/96h

 EC50 - for Crustacea
 > 398 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 294 mg/l/72h 96h

### 12.2. Persistence and degradability

EPOXY RESIN (Number average MW <= 700 )

NOT rapidly degradable



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 8 / 11

## SECTION 12. Ecological information .../>>

METHYLENE DIPHENYL BIS(DIMETHYL UREA) NOT rapidly degradable

#### 12.3. Bioaccumulative potential

EPOXY RESIN (Number average MW <= 700)

BCF 31

## 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09\* stickers and sealed sealing, containing organic solvents or other dangerous substances.

# **SECTION 14. Transport information**

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

### 14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700 ))
IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700 ))
IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700 ))



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 9 / 11

## SECTION 14. Transport information .../>>

### 14.3. Transport hazard class(es)

ADR / RID:

Class: 9

Label: 9

IMDG:

Class: 9

Label: 9

IATA:

Class: 9

Label: 9



### 14.4. Packing group

ADR / RID, IMDG, IATA:

Ш

#### 14.5. Environmental hazards

ADR / RID:

**Environmentally Hazardous** 

IMDG:

Marine Pollutant

IATA:

**Environmentally Hazardous** 



### 14.6. Special precautions for user

ADR / RID:

HIN - Kemler: 90

Limited Quantities: 5 L

Tunnel restriction code: (-)

IMDG:

Special provision: -EMS: F-A, S-F Cargo:

Limited Quantities: 5 L Maximum quantity: 450 L Maximum quantity: 450 L

Passengers: Maximum quantity: 450 Special provision: A97, A158, A197, A215 Packaging instructions: 964
Packaging instructions: 964

# 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

;

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

#### E١



# **Permabond Engineering Adhesives**

# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 10 / 11

# SECTION 15. Regulatory information .../>

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1 Skin sensitization, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2 Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H319 Causes serious eye irritation.H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

**EUH205** Contains epoxy constituents. May produce an allergic reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament



# Permabond ES578

Revision nr.1 Dated 27/10/2023 First compilation Printed on 27/10/2023 Page n. 11 / 11

## SECTION 16. Other information .../>>

- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.