

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

LOCTITE STYCAST 1266 PTB known as STYCAST 1266 PART B 220 G

SDS No. : 374519 V007.3 Revision: 24.07.2024 printing date: 08.10.2024 Replaces version from: 06.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE STYCAST 1266 PTB known as STYCAST 1266 PART B 220 G UFI: CNS1-5XC3-U208-N49S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):	
Skin corrosion	Category 1B
H314 Causes severe skin burns and eye damage.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



3,3'-Oxybis(ethyleneoxy)bis(propylamine)

Signal word:	Danger
Hazard statement:	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.
Precautionary statement: Prevention	P280 Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement: Response	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Kinse skin with water [of shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
3,3'- Oxybis(ethyleneoxy)bis(propyla mine) 4246-51-9 224-207-2 01-2119963377-26	50- 100 %	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	dermal:ATE = 2.500 mg/kg	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists. Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. **7.2. Conditions for safe storage, including any incompatibilities** Ensure good ventilation/extraction. Keep container tightly sealed. Refer to Technical Data Sheet.

7.3. Specific end use(s)

Epoxy adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period					Remarks
			mg/l	ppm	mg/kg	others	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (freshwater)		0,22 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (marine water)		0,022 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (intermittent releases)		2,2 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sewage treatment plant (STP)		125 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (freshwater)				1,1 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (marine water)				0,11 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Soil				0,091 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - systemic effects	exposure -		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Acute/short term exposure - systemic effects		176 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - local effects		13 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - systemic effects	17 mg/m3		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - systemic effects		52 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - local effects		0,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - local effects		6,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	oral	Long term exposure - systemic effects		5 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	yellow
Odor	amine-like
Physical state	liquid
Melting point	-32 °C (-25.6 °F)
Solidification temperature	< -20 °C (< -4 °F)
Initial boiling point	Not applicable, Decomposes before boiling point is reached
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	178,5 °C (353.3 °F)
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
рН	Not applicable, Product reacts with water.
Viscosity (kinematic)	6 - 13 mm2/s
(20 °C (68 °F);)	
Solubility (qualitative)	Soluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	3 mm hg;None
(20 °C (68 °F))	
Density	1,01 g/cm3 no method / method unknown
(20 °C (68 °F))	
Relative vapour density: (20 °C)	>1
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with alcohols and amines. Reacts with oxidants, acids and lyes Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

10.2. Chemical stability

Stable under recommended storage conditions.

Page 7 of 13

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid No decomposition if stored and applied as directed.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Hydrocarbons carbon oxides. nitrogen oxides Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	LD50	3.160 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	LD50	> 2.150 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	Sub-Category 1B (corrosive)		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

No data available.

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL P 600 mg/kg	screening	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL < 100 mg/kg	oral: gavage	59 days daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

0 L 0 P 7	Value type	Value	Exposure time	Species	Method
	LC50	> 215 - 464 mg/l	96 h	Leuciscus idus	DIN 38412-15

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(propy	EC50	218 mg/l	48 h	1 0	EU Method C.2 (Acute Toxicity for Daphnia)
lamine) 4246-51-9					

Chronic toxicity (aquatic invertebrates):

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC50	666 mg/l		Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	NOEC	15,6 mg/l		Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
3,3'-	EC10	152,5 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8
Oxybis(ethyleneoxy)bis(propy		-		-	(Pseudomonas
lamine)					Zellvermehrungshemm-
4246-51-9					Test)

12.2. Persistence and degradability

The product is not biodegradable.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	not inherently biodegradable	aerobic	< 20 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	not readily biodegradable.	aerobic	0 %	60 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

No data available.

No substance data available.

12.4. Mobility in soil

Cured adhesives are immobile.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	-1,25	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
4246-51-9	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1.	UN number or	r ID number
	ADR	2735
	RID	2735
	ADN	2735
	IMDG	2735
	IATA	2735
14.2.	UN proper shi	pping name
	ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'- oxybis(ethyleneoxy)bis(propylamine))
	RID	AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'- oxybis(ethyleneoxy)bis(propylamine))
	ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'- oxybis(ethyleneoxy)bis(propylamine))
	IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'- oxybis(ethyleneoxy)bis(propylamine))
	IATA	Amines, liquid, corrosive, n.o.s. (3,3'-oxybis(ethyleneoxy)bis(propylamine))
14.3.	Transport haz	ard class(es)
	ADR	8
	RID	8
	ADN	8
	IMDG	8
	IATA	8
14.4.	Packing group	
	ADR	II
	RID	II
	ADN	II
	IMDG	II
	IATA	II
14.5.	Environmenta	l hazards
	ADR	not applicable
	RID	not applicable
	ADN	not applicable
	IMDG	not applicable
	IATA	not applicable
14.6.	Special precau	itions for user
	ADR	not applicable
	<i>mun</i>	Tunnelcode: (E)
	RID	not applicable
	ADN	not applicable
	IMDG	not applicable
	IATA	not applicable
	1/11/1	not upprouoto

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

VOC content (2010/75/EC) < 3 %

Not applicable Not applicable Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.