

Ag	Cu	Ni	Sn
----	----	----	----

## Shieldex® Wrapped Yarn - coaxial

200471011717 Preliminary



Material	Nylon 6.6
Core Material	117/17 2 ply HCB TPU
Wrapped Material	117/17 2 ply HCB
Metal Plated	99.9 % Pure Silver
TPU Coating	Thermoplastic Polyurethane (TPU) transparent
+ B Coating	Nitrile rubber as additional protective coating
Yarn count silverized	3.290 dtex $\pm$ 5 %
Electrical Resistivity	< 300 $\Omega$ /m
Yield	3000 m /kg $\pm$ 10 %
Tenacity	44 $\pm$ 5 cN
Elongation / Break	23 % $\pm$ 5
Make Up	8 inch cross bobbin
Packaging	On request
Storage and Handling	According to our care and handling instructions
Compliance and Certification	DIN EN ISO 9001:2015, REACH, RoHS

Supplied by:  
[www.hitek-ltd.co.uk](http://www.hitek-ltd.co.uk)  
+44 (0)1724 851678



**HITEK**  
ELECTRONIC MATERIALS LTD

**Alterations Reserved 04.11.21/01** – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at [www.shieldex.de](http://www.shieldex.de).