



VpCI®-323

PRODUCT DESCRIPTION

VpCI-323 is a vapour phase corrosion inhibiting oil-based concentrate for use with working engine systems. VpCI-323 provides excellent protection in indoor and outdoor atmosphere conditions.

VpCI-323 protects in two unique ways. First, oil-soluble corrosion inhibitors offer a tenacious film which clings to metal surfaces, giving excellent contact corrosion protection. In addition to this film barrier, Cortec VpCIs release vapour phase corrosion inhibitors into the air above the oil. These VpCIs attach electrochemically to the metal surface for additional corrosion protection.

FEATURES

- Metal-free
- Low viscosity
- Universal corrosion protection to ferrous and non-ferrous metals
- Does not contain hazardous chromates, nitrites or phosphate inhibitors
- High flash point
- Non-toxic and thermally stable, providing long-lasting contact and vapour phase corrosion inhibitors
- Will pass through a filter mesh size of 1 micron
- Protects metals in a corrosive gas environment (H₂S)

TYPICAL APPLICATIONS

Working engines:

Add VpCI-323 to oil at a ratio of 1 part VpCI-323 to 10 parts oil for 24 months protection.

Tanks, gearboxes, differentials - stored or shipped dry:

Fog cavity interior with VpCI-323 concentrate using 1 liter per 35 ft³ (1.1 m³) of enclosed space.

METHOD OF APPLICATION

- Fill reservoirs to 10% below full capacity.
- Add VpCI-323 to reservoir at determined dosage (>10% reservoir capacity).
- Cap reservoirs as usual.
- Run vehicle or equipment a minimum of 15 minutes to circulate oil thoroughly throughout system.
- The product should be sealed before storage. The shelf life of VpCI-323 is up to 24 months.

TYPICAL PROPERTIES

Appearance	Clear yellow to amber liquid
Corrosion Resistance	Up to 24 months
Coverage	1260-1370 ft ² /gal (31-34 m ² /l)
Film Thickness	0.5-1 mil (12.5-25 microns)
Film Type	Oily
Flash Point	>212°F (>100°C)
Non-volatile Content	91-97%
Odor	Petroleum
Removal Method	Petroleum solvents Cortec® alkaline cleaners
Density	7.7-7.9 lb/gal (0.92-0.95 kg/l)

METALS PROTECTED

Carbon Steel	Copper
Stainless Steel	Cadmium
Galvanized Steel	Magnesium
Aluminium	Silver
Brass	Zinc

PACKAGING AND STORAGE

VpCI-323 concentrate is available in 5 gallon (19 liter) plastic containers, 55 gallon (208 liter) metal drums, totes and bulk. VpCI-323 should be stored sealed. Shelf life is 24 months in sealed drums.

**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE.

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Distributed by:

Supplied by:
www.hitek-ltd.co.uk
+44 (0)1724 851678



HITEK
ELECTRONIC MATERIALS LTD